



Printed marks(印刷):
 First Barcode 第一行EEMB
 Third Barcode 第三行 Voltage 电压 Capacity 容量
 Third Barcode 第三行 Voltage 电压 Capacity 容量
 Third Barcode 第三行 Voltage 电压 Capacity 容量
 Third Barcode 第三行 Voltage 电压 Capacity 容量

Model:	LP503870		Overcharge Detection Voltage(V) 过充保护电压(V)	4.28±0.05
Battery pack specification (电池组规格)	Min. Capacity 最低容量(mAh) (0.2C, 25±3°C) Single cell capacity (单体电芯容量)	1400	Overdischarge Detection Voltage(V) 过放保护电压(V)	3.0±0.1
	Typical Capacity 典型容量(mAh) (0.2C, 25±3°C) Single cell capacity (单体电芯容量)	1500	Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 2.0 (A)	constant (A) 持续 1.0 (A)
Ambient Conditions (环境温度)	Nominal Voltage 标称电压(V)	3.7	Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 2.0 (A)	constant (A) 持续 (A)
	Internal Impedance 内阻(≡) (mΩ, AC 1KHz)	300	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate battery application. The application profile is important for an appropriate battery application. The application profile is important for an appropriate battery application. The application profile is important for an appropriate battery application.	
	Charge Temp. 充电温度(°C)	0~45	情况对PCM的设计至关重要	
	Discharge Temp. 放电温度(°C)	-20~60		
	Humidity(湿度)	65±20%		

Remark(备注):
 1. No scratch, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. RoHS compliant(严格按照ROHS要求生产).

截止电压2.8V, 最大放电电流2A, 充电电流500mA

EEMB BATTERY		Drawn:	Sophie	Revise No.:	E4-2009
Title	LP503870-PCM-NTC-LDI	Checked 1:	Aily	Projection:	
File NO.	A09277	Checked 2:	Sophie	Pages:	1/1
		Approved:	Sophie	Scale:	1.5:1
		Draw Date:	2014/03/01	Unit:	mm