

65W POE injector

POE Injector support "IEEE 802.3af/at" "POE++" POE



Main Features

- ◆ 2 port Gigabit RJ45 port, 1GE POE out+1GE data input port.
- ◆ Support Carrier Grade Wireless radios, PTZ camera, etc.
- ◆ Fluid Control: Full-duplex: IEEE 802.3x, Half-duplex: back pressure.
- ◆ Auto MDI/MDIX.
- ◆ Support port lightning protection.
- ◆ Store-and-forward.
- ◆ All ports support wire speed switch and jumbo frame transmission.
- ◆ Plug-and-play, self-adaption.

Specification

Power pin	12+/45+ 36-/78-
POE out	52V 1.25A
Power	65W
POE	IEEE802.3af/at POE++
Data pin	12364578
Power input	AC 100-240V 50/60HZ
Shell	Metal case
Port	1GE POE output+1GE data input
Function	Plug and Play, without configuration management Under-voltage, over-voltage, over current short circuit protection System Reliability : MTBF> 100k hours Comply to EN55022, CLASS BCE & RE

Environmental	Working Temperature : 0°C~40°C Storage temperature : -40°C~80°C Working Humidity : 10%~90% RH non-condensing Storage Humidity : 5%~90% RH non-condensing
Speed	Ethernet 10Mbps half-duplex, 20Mbps full-duplex Fast Ethernet 100Mbps half-duplex, 200Mbps full-duplex Gigabit Ethernet 2000Mbps full-duplex
Network Media	10Base-T: Pair 2 Category 3(cat 3) and above UTP/STP(≤150m) 100Base-TX: Pair 2 Category 5(cat 5) and above UTP/STP(≤150m) 1000Base-T: Pair 4 Category 5(Cat5e) and above UTP/STP(≤150m)
Product Size	182mm*72mm*39mm(L*W*H)
Weight	0.9Kg

Product Information

Product Details: 1GE POE out+1GE data input