



电气特性:
 1. 额定电压: 125 VAC RMS
 2. 额定电流: 1.5 AMP
 3. 接触电阻: 45 mΩ MAX.
 4. 绝缘电阻: 1000 MΩ MIN. @500 VDC
 5. 耐压强度: 1000 V AC 或 1500V DC RMS @ 0.5mA 50 Hz 或 60 Hz -4秒

材料特性:
 1. 成型材料: PBT黑色
 2. 耐材料: 黄铜, 厚度0.35mm;
 3. 耐材料: 接触区镀金 (保持导电性), 镀金, 镀镍电鍍等
 4. 可靠性: 最少50次插拔
 5. 插入/拔出力: 22N / 2.27kg Max;
 6. 额定电流: 57.83N Min.

环境特性:
 1. 储存温度: 0℃~+70℃
 相对湿度<80%
 2. 工作温度: -40℃~+85℃

NOTES:
ELECTRICAL:
 1. VOLTAGE RATING : 125 VAC RMS.
 2. CURRENT RATING : 1.5 AMP.
 3. CONTACT RESISTANCE : 45 MILLIOHMS MAX.
 4. INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC
 5. DIELECTRIC STRENGTH : 1000 V AC OR 1500V DC RMS @ 0.5mA 50 Hz / 60 Hz 1 Minute

MECHANICAL:
 1. HOUSING&INSERT& MATERIAL : PBT . COLOR BLACK
 2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.35mm.
 3. PLATING : 1: CONTACT AREA- SELECTIVE GOLD PLATING.
 2: TAILS PLATING TIN OVER NICKEL.
 4. OPERATING LIFE : 750 CYCLES MIN.
 5. MATING/UNMATING FORCE: : 22N / 2.27kg Max.
 6. RETENTION STRENGTH: : 57.83N Min.

ENVIRONMENTAL:
 1. STORAGE : 0°C TO +70°C RELATIVE HUMIDITY<80%.
 2. OPERATION : -40°C TO +85°C.
 MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
 ROHS PART NUMBER:

MOD SOCK 4-4USA

RoHS Compliant		5721 4P4C 无耳插座 (L脚)	
Material: 材质		NAME: 名称	
TOLERANCES 公差		DWG NO: 图号	
00~15 ±0.15	SEE NOTE	5721 4P4C	
15~30 ±0.20	SEE NOTE	REV. 版本	
30~ ±0.25	SHEET OF 第1页 共1页	01	
ANGLES: ±1°	FINISH: 电镀	PART NO: 料号	
DESIGNED: 设计		APPROVED: 核准	
CHECKED: 审核			

COMMUNICA (PTY) (LTD)
 A WORLD OF ELECTRONICS Reg. No. 1979/00371/07
 ■ HEAD OFFICE
 Tel (012) 657-3500
 Fax (012) 657-3550
 E-Mail: sales@communicaco.za
 Web: www.communicaco.za
 ■ CAPETOWN
 Tel (021) 447-0948
 Fax (021) 447-0959
 ■ PRETORIA
 Tel (012) 328-7008
 Fax (012) 328-7018