

Specification		
	Model	DVR XY9116H AHD 5.0MP
System	Main chip	Hi3531A
	OS	LINUX
	System Resources	Multi-channel Realtime recording, Multi-channel playback, Multi-channel network operation, USB Backup
Interface	Operation menu	16-bit true color graphical menu interface, mouse operation supported
	Display	1/4/8/9/16display (take the pure coaxial input mode as an example)
Video	Format	H.264
	Output	VGA (Max up to 1080P) ; HDMI (Max up to 4K)
	Preview	16*5M@20fps(AHD)/ 16*3M@18fps(AHD)/16*1080P(5 in 1)
	Recode	16*5M@11fps(AHD)/ 16*3M@10fps(AHD)/16*1080P @12fps (5 in 1) / 16*720P(5 in 1)
	Decord	8*5M@8fps(AHD)/ 8*3M@10fps(AHD)/16*1080P @12fps (5 in 1) / 16*720P(5 in 1)
	Multi-mode Input	AHD: 16*5M: 20fps Hybrid: 8*5M (CVBS) +8*5M (IP) NVR: 16*5M
	Motion Detect	Each view window can set 192 (16*12) detection area,can set multi-level sensitivity (only for local channel)
Audio	Audio	G.711A
	Intercom	Support
Record and Playback	Recording mode	Manual、Alarm、Motion Detect、Timer
	Local playback	8 Channel (when Analog mode)
	Video search	Time, Date,Event,Channel search
Storage and Backup	Storage	Local HDD, Network
	Backup	Network backup, external HDD, USB Drive, HDD
Port	Video Input	16 * BNC
	Video Output	1 * VGA, 1 * HDMI
	Spot Monitor	no
	Audio Input	4* RCA
	Audio Output	1 * RCA
	Alarm Input	8 channels
	Alarm Output	1 channel
	Network port	RJ45 10M/100M
	PTZ Control	1 * RS485 Support multipal PTZ Contract
	USB port	2 * USB Port
	HDD Port	2 * SATA hdd ports (up to 6T for each one)
	Wireless Port	3G、WIFI(can be USB WIFI Dongle)
Others	Power	1 * HDD: 12V/2A 2 * HDD: 12V/5A 4 * HDD: 12V/6A
	Power consumption	Less than 15W (no HDD)
	Working temperature	0℃—+55℃
	Working humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa
	packing Size	56.7*-36.7*32.6cm
	Weight	13kg