Mil-C-26482 Insert Arrangements

Insert Rating Contacts	6-1 I 1x20	8-2* I 2x20	8-3* I 3x20	8-4* I 4x20	8-33* I 3x20	8-98*** I 3x20	10-2^^^ I 2x16	10-5** I 5x20	10-6* I 6x20	10-7^^^ I 7x20	10-8^^^ I 8x20	10-98*** I 6x20	12-3* II 3x16
													
Insert Rating Contacts	12-4** I 4x16	12-8**** I 8x20	12-10* I 10x20	12-12^^^ I 12x20	12-14^ I 14x20	14-4** I 4x12	14-5* II 5x16	14-9 I 5x20 4x12	14-12**** I 8x20 4x16	14-15**** I 14x20 1x16			
													
Insert Rating Contacts	14-18*** I 18x20	14-19**** I 19x20	14-22** I 1x20 4x12	14-91HV 5kVAC(RMS) 3x20	16-8**** II 8x16	16-23* I 22x20 1x16	16-26* I 26x20	16-76 1K5VAC(RMS) 8x20 1x12 5x12(Coax)					
													
Insert Rating Contacts	16-99** I 21x20 2x16	18-5** II 5x12	18-8** I 8x12	18-11* II 11x16	18-30*** I 29x20 1x16	18-32* I 32x20	18-71 Coax 1x8(Coax) 8x16	18-76 II 3x12(Coax) 1x8(Coax)					
													
Insert Rating Contacts	18-80 II 6x20 2x8(Coax)	18-91 HV 5KVAC(RMS) 6x20	20-16* II 16x16	20-24*** I 24x20	20-25*** I 25x20	20-27**** I 27x20	20-39*** I 37x20 2x16	20-41* I 41x20					
													
Insert Rating Contacts	20-70 Coax 10x20 4x8(Coax)	20-90 I 7x20	22-7 I 7x8(Coax)	22-12 I 12x12	22-19 I 19x12	22-21* II 21x16	22-25** I 23x16	22-32*** I 32x20					
													
Insert Rating Contacts	22-34*** I 34x20	22-36*** I 36x20	22-41*** I 27x20 14x16	22-55* I 55x20	22-71 Coax 2x20 7x8(Coax)	22-78 I 7x8(Coax)	22-95 I 26x20 6x12						
													
Insert Rating Contacts	22-96** II 7x12	24-19 II 19x12	24-31^^ I 31x16	24-61* I 61x20									

Contact Legend
Front end of pins illustrated

Miniature Cylindrical Connectors Additional Information

Mil-C-26482 Series 1
MS/PT/62GB/62IN – Bayonet coupling, solder contacts
MS/PT-SE – Bayonet coupling, rear insertion/front release crimp removable contacts

Mil-C-26482 Series 2
MS/PTS-DR – Bayonet coupling, rear insertion/rear release crimp removable contacts with dielectric retention

Proprietary
PT – Bayonet coupling, solder contacts
SP – Same as PT with large flange and mounting holes
PT-SE – Bayonet coupling, rear insertion/front release crimp removable contacts, individual retention towers
SP-SE – Same as PT-SE with large flange and mounting holes
PT-CE – Bayonet coupling, rear insertion/front release crimp removable contacts, nylon wafer retention
SP-CE – Same as PT-CE with large flange and mounting holes
PC – Double-stub threaded coupling, solder contacts
PC-SE – Double-stub threaded coupling, rear insertion/front release crimp removable contacts, individual retention towers
PC-CE – Double-stub threaded coupling, rear insertion/front release crimp removable contacts, nylon retention
AIPT Series – Low cost Mil-C-26482 type, designed for the industrial marketplace

^AAO/ASF/AIIPL ^^AAO/AIIPL/ADS ^^^AIIPL/AAO *AAO/ASF/LTD/AIIPL/ADS **AAO/ADS ***AAO/ASF/ADS ****AAO/ASF/AIIPL/ADS