

TCM02 400A AC/DC

- Jaw Size 30mm
- Auto zero adjustment
- Data hold
- Diode
- Continuity

CAT II
600V
IEC61010-1



Technical Specification

DC/AC Current	40,400A
DC/AC Voltage	2,4,24,240,600V
Resistance	400,4K,40K,200KΩ
Frequency	999KHz
Accuracy	
AC/DC Current	±2.5% ± 5 Digit
AC/DC Voltage	±1.5% ± 5 Digit
Resistance	±1.2% ± 5 Digit
Frequency	±0.1% ± 3 digits
Protection	
AC/DC Current	400V AC
DC Voltage	600V AC
AC Voltage	800V AC
Other Ranges	600V AC

Model Specification

Dimensions (mm)	190(L) x 64(W) x 30(H)
Power Source	9V Battery
Weight	175g

T2102 600A AC/DC

- Jaw Size 30mm
- Diode
- Continuity
- Data hold
- Zero mode
- Auto power off

CAT II
600V
IEC61010-1



Technical Specification

DC/AC Current	40,600A
DC/AC Voltage	2,4,24,240,600V
Resistance	400,4K,40K,200K,2.4MΩ
Frequency	5MHz
Accuracy	
AC/DC Current	±2.5% ± 5 Digit
AC/DC Voltage	±1.5% ± 5 Digit
Resistance	±1.2% ± 5 Digit
Frequency	±0.1% ± 3 digits
Protection	
AC/DC Current	400V AC
DC Voltage	600V AC
AC Voltage	800V AC
Other Ranges	600V AC

Model Specification

Dimensions (mm)	190(L) x 64(W) x 30(H)
Power Source	9V Battery
Weight	175g

T8056 1000A AC/DC

- Jaw Size 42mm
- Duty Cycle
- Diode
- Continuity
- Auto Power Off
- Relative Zero
- Data Hold

CAT III
600V
IEC61010-1



Technical Specification

DC/AC Current	400,1000A
DC Voltage	400m,4,40,400,1000V
AC Voltage	4,40,400,700V
Resistance	400,4K,40K,400K,4m,40MΩ
Frequency	40,400,4k,40K,100KHz
Temperature	-40°C to 750°C
Capacitance	4n,40n,400n,4μ,40μF
Accuracy	
DC Current	±3,0% + 3 Digit
AC Current	±3,0% + 3 Digit
DC Voltage	±0,8% + 3 Digit
AC Voltage	±1,0% + 10 Digit
Resistance	±2,0% + 3 Digit
Frequency	±2,0% + 1 Digit
Temperature	±1,0% + 6 Digit
Capacitance	±4,0% + 10 Digit
Protection	
AC/DC Voltage	1000V DC or 700V AC RMS
AC/DC Current	120% For 60 Seconds

Model Specification

Accessories	Carry Case & Temp Probe
Dimensions (mm)	250(L) x 99(W) x 43(H)
Power Source	9V Battery
Weight	480g

T2138 1000A AC/DC

- Jaw Size 40mm
- Back Light and Clamp Light
- Data Hold
- Resistance
- Frequency
- Overmould
- Diode



Technical Specification

AC/DC Current	1,400,600,1000A
AC Voltage	4,40,400,600,700V
DC Voltage	4,40,400,600,1000V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	40,400,4K,40K,100KHz
Accuracy	
AC/DC Current	± 3 % + 5 Digit
AC/DC Voltage	± 0.8 % + 5 Digit
Resistance	± 1 % + 5 Digit
Frequency	± 0.1 % + 1 Digit
Protection	
AC/DC Current	120% Ranges for 60 Sec
AC/DC Voltage	1000V DC or 700V AC RMS
Resistance	250V DC RMS AC for all ranges
Frequency	1V to 10V RMS 40Hz to 100KHz

Model Specification

Accessories	Carry Pouch
Dimensions (mm)	225(L) x 86(W) x 32(H)
Power Source	3 x 1.5V AAA Batteries
Weight	320g