

T70 Phase Sequence Indicator & Voltage Detector

- Detection AC voltage from 100V to 1000V to ground
- Phase sequence and conformity test with 1 wire method
- Working frequency: 50/60Hz
- With or without contact measurements
- LED red and buzzer indication
- Practical pen clip
- Safety: IEC/EN61010-1, CAT IV 1000V

NEW

CAT IV 1000V IEC61010-1



Incorrect phase sequence

Correct phase sequence



Application video



<http://www.hellermanntyton.co.za/downloads.html>

T534 Circuit Breaker Identifier

- Tracing plug sockets to circuit breakers
- Battery check
- Signal strength buzzer
- Calibrate function by moving receiver across circuit breakers
- Wiring indications



Meter Supplied With Certificate of Conformance

Technical Specification

Operating Voltage	200 - 250 VAC
Frequency	47 - 63Hz
Duty Cycle	10µs
Transmitter Power	Wall Socket
Receiver Power	9V Battery

Model Specification

Dimensions (mm)	(TX) 200(L) x 60(W) x 45(H)
Dimensions (mm)	(RX) 65(L) x 50(W) x 30(H)
Power Source	(TX) 9 V Battery (RX) Mains
Weight	135g

T6236 Digital Tachometer

- Low cost
- Photo/contact
- Removable contact head
- Back light



Technical Specification

Measurement & Range	Photo: 2.5 to 999999 RPM Contact: 0,5 to 19999 RPM Surface Speeds (m/min): 0,01 to 99,99 m/min
Resolution RPM	0,1 (0,5 to 999,9 RPM)
M/Min	0,01 (0,05 to 99,99 m/min)
Display	5 Digits, 18mm LCD
Accuracy	± (0,05% + 1 Digit)
Memory	Last/Max/Min value

Model Specification

Accessories	Carry Case Reflecting tape marks (600mm) RPM adaptor (cone) RPM adaptor (Funnel) Surface speed test wheel
Dimensions (mm)	210(L) x 74(W) x 37(H)
Power Source	4 x 1,5V AA Batteries
Weight	200g

T2238 Digital Tachometer

- Photo/contact
- Microprocessor based
- High accuracy
- Variable LCD contrast
- Holds last reading/recalls max & min



TAS35C
Surface Speed
Test Wheel

TMTL35A
Metal
Shaft of
Cone

TAS35B
RPM
Adaptor
(Funnel)

TA535A
RPM
Adaptor
(Cone)



Technical Specification

Measurement & Range	Photo: 5 to 99,999 RPM Contact: 0,5 to 19,999 RPM Surface Speed (m/min): m/min: 0,05 to 199,9 m/min ft/min: 0,2 to 6,560 ft/min
Resolution RPM	0,1 RPM (<1,000 RPM)
M/Min	1 RPM (≥ 1000 m/min) 0,01 m/min (< 100 m/min.)
Ft/min	0,1 m/min (≥ 100 m/min.) 0,1 ft/min. (< 1,000 ft/min.) 1 ft/min. (≥ 1,000 ft/min.)
Display	5 Digits, 10 mm (0,4") LCD
Accuracy	± (0,05% + 1 Digit)
Memory	Last/Max/Min value

Model Specification

Accessories	Carry Case Reflecting tape marks (600mm) RPM adaptor (cone) RPM adaptor (Funnel) Surface speed test wheel
Dimensions (mm)	195(L) x 61(W) x 39(H)
Power Source	4 x 1,5V AA Batteries
Weight	280g