



\*\*\* Spare part \*\*\* SIMATIC DP, 5 electronic modules for ET 200S, 2 DI Standard 24 V DC, 15 mm width, 5 units per packing unit

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Type of output voltage	min. L+ (-0.5 V), under load
Output current	
<ul style="list-style-type: none"> <li>Rated value</li> </ul>	500 mA
<ul style="list-style-type: none"> <li>permissible range, lower limit</li> </ul>	0 mA
<ul style="list-style-type: none"> <li>permissible range, upper limit</li> </ul>	500 mA
Power loss	
Power loss, typ.	0.4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	1 byte
<ul style="list-style-type: none"> <li>with packing</li> </ul>	2 bit
Digital inputs	
Number of digital inputs	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
<ul style="list-style-type: none"> <li>Type of input voltage</li> </ul>	DC
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0"</li> </ul>	-30 to +5 V
<ul style="list-style-type: none"> <li>for signal "1"</li> </ul>	+15 to +30 V
Input current	
<ul style="list-style-type: none"> <li>for signal "1", typ.</li> </ul>	7 mA; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> <li>parameterizable</li> </ul>	No
<ul style="list-style-type: none"> <li>at "0" to "1", min.</li> </ul>	2 ms; typically 3 ms
<ul style="list-style-type: none"> <li>at "0" to "1", max.</li> </ul>	4.5 ms
<ul style="list-style-type: none"> <li>at "1" to "0", min.</li> </ul>	2 ms; typically 3 ms
<ul style="list-style-type: none"> <li>at "1" to "0", max.</li> </ul>	4.5 ms
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	600 m
Encoder	

<b>Connectable encoders</b>	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
<b>Diagnostics indication LED</b>	
• Group error SF (red)	No
• Status indicator digital input (green)	Yes; per channel
<b>Parameter</b>	
Remark	1 byte
<b>Potential separation</b>	
Potential separation digital inputs	
• between the channels	No
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Dimensions</b>	
Width	15 mm
Height	81 mm
Depth	52 mm
<b>Weights</b>	
Weight, approx.	35 g
<b>Classifications</b>	

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

General Product Approval



[Miscellaneous](#)

[Manufacturer Declaration](#)

[China RoHS](#)



General Product Approval      EMV      For use in hazardous locations



[FM](#)



For use in hazardous locations      Maritime application



UL



ATEX



IECEX

[Miscellaneous](#)

[CCC-Ex](#)



ABS

Maritime application



BUREAU  
VERITAS



DNV



LRS

[NK / Nippon Kaiji Kyokai](#)



PRS



RINA

Maritime application

[CCS \(China Classification Society\)](#)

last modified:

7/1/2025