

THICK FILM CHIP RESISTOR

Features

- Small size and lightweight
- Suitable for both flow and re-flow soldering
- Reduction of assembly costs and matching with placement machines



Ordering Procedure: (Ex.: 1206, 1/4W-S, +/-5%, 1.2Ω, T/R-5000)

1	2	0	6	S	4	J	0	1	2	J	T	5	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---

Resistor Type:
Fill in these 4 digits with the Chip Resistor types as follows:
0402, 0603, 0805, 1206, 1210, 2010, 2512, 2D02, 4D02, 4D03, 10P8, 16P8

Resistance Value:

- E-24 series: the 1st digit is "0", the 2nd & 3rd digits are for the significant figures of the resistance and the 4th indicate the numbering of the zeros following;
- E-96 series: the 1st to 3rd digits are for the significant figures of the resistance and the 4th digit indicate the number of zeros following.

Decimal point is expressed by:
"J" ~ 0.1, "K" ~ 0.01, "L" ~ 0.001
Ex. 012J ~ 1Ω2, 226K -- 2Ω26

Wattage:
Fill in these 2 digits with the Codes as follows:
Normal size: WH=1/32W, WG=1/16W, WA=1/10W, W8=1/8W, W4=1/4W, W2=1/2W, 1W=1W
Small size: SA=1/10W-S, S8=1/8W-S, S4=1/4W-S, S3=1/3W-S, 07=3/4W-S

Tolerance:
F = ±1%, G = ±2%, J = ±5%

Packing Type:
T =T/R packing
B =Bulk in Poly-bag
C =Bulk in cassette

Packing Qty:
1 = 1,000 pcs, 2 = 2,000 pcs, 3 = 3,000 pcs, 4 = 4,000 pcs, 5 = 5,000 pcs, : : 9 = 9,000 pcs,
A = 500 pcs, B = 2,500 pcs, C = 10,000 pcs, D = 20,000 pcs


Special Feature:
0 = NIL
E = Lead (Pb) Free Plating Type

Note:


1. Special resistance tolerance requirement available on a case-to-case basis. Please indicate when ordering.
2. Special T.C.R. requirements can be supplied on a case-to-case basis. Please indicate when ordering.
3. "Lead Free Plating" type is available now on a case to case basis, please consult factory for The specification.

THICK FILM CHIP RESISTOR

Construction




Power Rating & Dimension



Type	Power Rating at 70°C	Max. Working Voltage	Max. Overload Voltage	Operating Temp. (°C)	Tolerance %	Resistance Range	Standard Series	Dimension (mm)				
								L	W	H	ℓ ₁	ℓ ₂
0402	1/16W	25V	50V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 100 Ω - 1M Ω 2 Ω - 3.3M Ω 2 Ω - 3.3M Ω	E-96 E-24 E-24	1.00±0.10	0.50±0.05	0.35±0.05	0.20±0.10	0.25±0.10
0603	1/10W-S 1/16W	50V	100V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 10 Ω - 1M Ω 10 Ω - 1M Ω 1 Ω - 10M Ω	E-96 E-24 E-24	1.60±0.10	0.80 +0.15 -0.10	0.45±0.10	0.30±0.20	0.30±0.20
0805	1/8W-S 1/10W	150V	300V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 10 Ω - 1M Ω 10 Ω - 1M Ω 1 Ω - 10M Ω	E-96 E-24 E-24	2.00±0.15	1.25 +0.15 -0.10	0.55±0.10	0.40±0.20	0.40±0.20
1206	1/4W-S 1/8W	200V	400V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 10 Ω - 1M Ω 10 Ω - 1M Ω 1 Ω - 10M Ω	E-96 E-24 E-24	3.10±0.15	1.55 +0.15 -0.10	0.55±0.10	0.45±0.20	0.45±0.20
1210	1/3W-S 1/4W	200V	400V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 10 Ω - 1M Ω 1 Ω - 10M Ω 1 Ω - 10M Ω	E-96 E-24 E-24	3.10±0.10	2.60±0.15	0.55±0.10	0.50±0.25	0.50±0.20
2010	3/4W-S 1/2W	200V	400V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 10 Ω - 1M Ω 1 Ω - 10M Ω 1 Ω - 10M Ω	E-96 E-24 E-24	5.00±0.10	2.50±0.15	0.55±0.10	0.60±0.25	0.50±0.20
2512	1W	200V	400V	-55~+125	Jumper ±1 ±2 ±5	< 50 m Ω 10 Ω - 1M Ω 1 Ω - 10M Ω 1 Ω - 10M Ω	E-96 E-24 E-24	6.35±0.10	3.20±0.15	0.55±0.10	0.60±0.25	0.50±0.20

Derating Curve



THICK FILM CHIP RESISTOR

Multiplier Code (for 0603 1% marking)

Code	A	B	C	D	E	F	G	H	X	Y	Z
Multiplier	10 ⁰	10 ¹	10 ²	10 ³	10 ⁴	10 ⁵	10 ⁶	10 ⁷	10 ⁻¹	10 ⁻²	10 ⁻³

Standard E-96 Series Resistance Value Code (for 0603 1% marking)

Ω Value	Code	Ω Value	Code	Ω Value	Code	Ω Value	Code	Ω Value	Code
100	01	162	21	261	41	422	61	681	81
102	02	165	22	267	42	432	62	698	82
105	03	169	23	274	43	442	63	715	83
107	04	174	24	280	44	453	64	732	84
110	05	178	25	287	45	464	65	750	85
113	06	182	26	294	46	475	66	768	86
115	07	187	27	301	47	487	67	787	87
118	08	191	28	309	48	499	68	806	88
121	09	196	29	316	49	511	69	825	89
124	10	200	30	324	50	523	70	845	90
127	11	205	31	332	51	536	71	866	91
130	12	210	32	340	52	549	72	887	92
133	13	215	33	348	53	562	73	909	93
137	14	221	34	357	54	576	74	931	94
140	15	226	35	365	55	590	75	953	95
143	16	232	36	374	56	604	76	976	96
147	17	237	37	383	57	619	77		
150	18	243	38	392	58	634	78		
154	19	249	39	402	59	649	79		
158	20	255	40	412	60	665	80		

Marking on the Resistors Body:

- For 0402 size, no marking on the body due to the small size of the resistor.
- ±5% tolerance product. The marking is 3 digits, the first 2 digits are the significant figures of the resistance and the 3rd digit denotes number of zeros following:

153 = 15000Ω = 15KΩ; 120 = 12Ω



Below 10Ω shown as this: 6R8 = 6.8Ω



- ±1% tolerance of 0805 above. The marking is 4 digits, the first 3 digits are the significant figures of the resistance and the 4th digit denotes number of zeros following:

2372 = 23700Ω = 23.7KΩ; 1430 = 143Ω

Below 10Ω shown as this: 3R24 = 3.24Ω




THICK FILM CHIP RESISTOR

- Standard E-96 series values ($\pm 1\%$ tolerance) of 0603 size. Due to the small size of the resistor's body, 3 digits marking will be used to indicate the accurate resistance value by using the following Multiplier & Resistance Code.

So the resistance value are marked as the following samples:

$$1.96\text{K}\Omega = 196 \times 10^1 \Omega = \mathbf{29B}$$




$$12.4\Omega = 124 \times 10^{-1} \Omega = \mathbf{10X}$$



*Standard E-24 and not belong to E-96 series values (in $\pm 1\%$ tolerance) of 0603 size. The marking is the same as 5% tolerance but marking as underline.

$$\underline{\mathbf{122}} = 1200 = 1.2\text{K}\Omega$$



$$\underline{\mathbf{680}} = 68\Omega$$



Performance Specifications

Temperature coefficient	$\pm 5\%$: $1\Omega \sim 10\Omega \leq \pm 400\text{PPM}/^\circ\text{C}$; $11\Omega \sim 10\text{M}\Omega \leq \pm 200\text{PPM}/^\circ\text{C}$ $\pm 1\%$: $10\Omega \sim 100\Omega \leq \pm 200\text{PPM}/^\circ\text{C}$; $101\Omega \sim 1\text{M}\Omega \leq \pm 100\text{PPM}/^\circ\text{C}$
Short-time overload	$\pm 5\%$: $\pm(2.0\% + 0.1\Omega)$ Max. $\pm 1\%$: $\pm(1.0\% + 0.1\Omega)$ Max.
Insulation resistance	$\geq 1,000$ Mega Ohm
Dielectric withstanding voltage	No evidence of flashover, mechanical damage, arcing or insulation breakdown.
Terminal bending	$\pm(1.0\% + 0.05\Omega)$ Max.
Soldering heat	Resistance change rate is $\pm(1.0\% + 0.05\Omega)$ Max.
Solderability	Min. 95% coverage
Temperature cycling	$\pm 5\%$: $\pm(1.0\% + 0.05\Omega)$ Max. $\pm 1\%$: $\pm(0.5\% + 0.05\Omega)$ Max.
Humidity (Steady State)	$\pm 5\%$: $\pm(3.0\% + 0.1\Omega)$ Max. $\pm 1\%$: $\pm(0.5\% + 0.1\Omega)$ Max.
Load life in humidity	$\pm 5\%$: $\pm(3.0\% + 0.1\Omega)$ Max. $\pm 1\%$: $\pm(1.0\% + 0.1\Omega)$ Max.
Load life	$\pm 5\%$: $\pm(3.0\% + 0.1\Omega)$ Max. $\pm 1\%$: $\pm(1.0\% + 0.1\Omega)$ Max.

* The values which are not of standard E-24 series (2% & 5%) and not of E-96 series (1%) could be offered on a case to case basis.

* For complete details, please see Page 69.