

TBM3030 600A AC

- Jaw size 26mm
- Large LCD display
- Diode
- Continuity
- Relative zero
- Data hold
- **Thinner jaws**

Technical Specification	
AC Current	40,600A
DC Voltage	400m,4,40,400,600V
AC Voltage	4,40,400,600V
Resistance	400,4K,40K,400K,4M,40MΩ
Frequency	5Hz to 100KHz
Capacitance	500n,5μ,50μ,500μ,3000μF
Accuracy	
AC Current	±1,9%+ 8 Digit
DC Voltage	±1,0%+ 4 Digit
AC Voltage	4,40,400V ±1,5% + 5 Digit 600V ±2,0% + 5 Digit
Resistance	4K,40K,400KΩ ± 0,6%+4 Digit 4MΩ ± 1,0% + 4 Digit 40MΩ ± 2,0% + 4 Digit
Frequency	± 0,5% + 4 Digit
Capacitance	± 3,5% + 6 Digit
Protection	
AC/DC Voltage	600V DC/AC RMS
Current	400A RMS CONTINUOUS
Transient Protection	6.5KV LIGHTNING SURGE (1.2/50 μs)



Model Specification	
Accessories	Carry Pouch
Dimensions (mm)	190(L) x 63(W) x 32(H)
Power Source	3V CR2032 (TBM BATT)
Weight	187g