



SPECIFICATION:

1. Insulation Resistance: Over 100MΩ at 500V DC.
2. Dielectric strength: 2000V AC 1 Minute.
3. Body Material: Thermoplastic 94V-2~V-0.
4. Withdrawal force: 30N~50N

Rating:AC 15A 250V	
Mark	Safety Regulation
	CULUS
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	ENEC
	CCC

DRAWING:C:DG\NEW-R\T-台北\R-302SN-H\R-302SN-H(07).DWG

<p>富灣股份有限公司 RICH BAY COMPANY LTD. 台北縣樹林市東興街57號 NO. 57, Tung Hsing St., Shu-Lin Town, Taipei Hsien, Taiwan, R. O. C. TEL:886-2-86867781~4 FAX:886-2-86867780 http://www.richbay.com.tw</p>	<p>DRAWN BY</p>	UNIT	UNIT Q'TY	SCALE	TOLERANCE X.XX±0.1 XX.XX±0.2 XXX.XX±0.3	PRODUCT NO.	R-302SN-H(07)	REV
		mm	1	1:1				
		RD	RD	RD				
		106.12.05	106.12.06	106.12.06				
		林文啟	張育誠		ID NO	171205A04	INTERIM NO.	
					DESCRIPTION		NEW NO.	