



GENERAL PURPOSE RELAY




57.02 57.04



57.02

57.04



Contact specification

Contact form	2Z、2H、2D、4Z、4H、4D
Contact resistance	≤100mΩ (1A 6VDC)
Contact material	AgCdO AgSnO ₂
Contact capacity	57.02:10A 250VAC/30VDC 57.04 5A 250VAC/30VDC

Technical specification

Insulation resistance	≥500MΩ (500VDC)
Dielectric strength	Between coil and contact ≥1500VAC1min
	Between open contacts ≥1000VAC1min
Operate / Release time	Between contacts of different poles ≥1500VAC1min
	≤25ms/25ms
Terminal type	PCB and socket mounting


DC Coil data

Nominal voltage	Operate voltage	Release voltage	Coil resistance
VDC	VDC	VDC	Ω ± 10%
5	4.0	0.5	28
6	4.8	0.6	40
12	9.6	1.2	160
24	19.2	2.4	640
48	38.4	4.8	2560
110	88.0	11.0	12100

AC Coil data

Nominal voltage	Operate voltage	Release voltage	Coil resistance
VAC	VAC	VAC	Ω ± 10%
6	4.8	1.8	12
12	9.6	3.6	42
24	19.2	7.2	168
48	38.4	14.4	675
110	96.0	36.0	3500
220/240	176.0	66.0	14000/16500

Matched Socket



RT702-B

RT704-B

Coil specification

Rated coil power	0.9W / 1.2VA
------------------	--------------


Outline dimension、Mounting holes (Bottom view)、 Wiring diagram (Bottom view)

57.02 Outline dimension


57.02 Mounting holes(Bottom view)

57.04 Outline dimension

57.02 Wiring diagram(Bottom view)



2Z



4Z