

ГLАŢ		ODUCT SHEET		
Flash Item No.:	BL/ZR-TG002		-	
	BL/21(-1 6002			
Description				
20W SMD LED SLIM F				
Auxiliary code:	BL/ZR-TG002			
	6009696367811			
Sample required when manufactured for the first time	n manufactured YES			
Dimensions				
_ength	150mm			
Width /Diameter	128mm		ARTWORK/PACKING SPECIFICATIONS	
Depth	38mm		Product History	Existing
Bracket Thickness	1,5mm		Packing	Box Packing
Specifications:	Rated		Purpose	Display
	Intergrated CC Driver BP Chip		Manual Required	Yes
	0,75mm ² 3 Core pure			Minimum Size Euro Hole - Flash Standard
Mains wire	Copper cable		Euro Hole Required	
Watt	20W			
Lumen Colour	1500lm Matt Black		PLEASE COMPLETE ALL SHADED AREAS FOR ARTWORK PURPOSES	
Beam Angle	120°		Length	158mm
Power Factor	>0.95		Width / Diameter	139mm
Voltage	230V 50Hz		Lid	44mm
Lifetime	3 years		Specifications	
IP Rating	IP65		Energy Rating	A
Colour Temp	6000K Daylight ± 150K		Watt	20W
			Lumen	1500lm
Rating Label		Symbols	Colour Temp	6000K Daylight
to be printed on the silver rating label (symbols height > = 5mm , text height > = 2mm)	Flash Logo	0.5m	IP Rating	IP65
	Item No: 230V 50Hz		ADDITIONAL INFORMATION	
	20W,IP65	X	ICONS: BEAM ANGLE , RECYCLE, NO BIN , CE . IP65	
	6000K Daylight			
	Production No: As per Order		WARNINGS: REFER TO INSTRUCTION BEFORE INSTALLATION	
Packing per Export C	arton		ļ	
UV Laminated	As per Flash Artwork		EXPORT CARTON SIDE MARKS	
Colour Box packing	INNER CARTON	EXPORT CARTON QTY	Quantity	
1 Pc	NO	30 Pcs	Weights and Measurements	
Protection in packing	As per Flash instruction	Virgin Material Only	Carto	on 1-Up
			Produ	ction No
			Line drawing of lamp on 2 sides of export carton	
			Flash Guarantee must cover 70% of Panel on 2 sides and be printed in Red & Black as per Flash Artwork	
			Slogan must be printed in Red on 2 sides as per Flash Artwork	
			Use Virgin Material Only	
1				
			MUST BE FITTED WITH 30CM 3 CORE WIRE, STRIPPED AND READY FOR TERMINATION	
			READY FOR BLACK GLASS PRINTED WITH	