

**datasheet for MLS WS 200/2,5**  
**article number: 934089102**

<b>product description:</b>	<b>order number: 934 089-102</b>
<b>description:</b>	Safety measuring lead to IEC 61010 standard, at either end 4 mm diameter safety connector with onward connection capability (4mm socket). Nickel-plated copper beryllium contact spring. Highly flexible, double insulated stranded lead, shatter-proof grip sleeve and lead. Built in color indicator for easy identification of insulation damages.
<b>typ:</b>	MLS WS 200/2.5 blau/blue
<b>system:</b>	4mm safety system
<b>order number:</b>	934 089-102
<b>color</b>	
<b>other color versions:</b>	
<b>technical data</b>	
<b>measurement category acc. to IEC 61010:</b>	CAT II
<b>pin dimensions</b>	4 mm
<b>type of contact:</b>	pin (spring loaded)
<b>cable type:</b>	LEH-XY
<b>cable specification:</b>	highly flexible lead
<b>wire stranding:</b>	320 x 0.10 mm
<b>rated voltage:</b>	AC/DC 1000 V
<b>rated current:</b>	32 A
<a href="#">Please consider derating curve!</a>	
<b>contact resistance:</b>	20 mOhm
<b>cable length:</b>	200 cm
<b>conductor size:</b>	2.5 mm <sup>2</sup>
<b>cable material:</b>	PVC
<b>cable color:</b>	blue
<b>material</b>	
<b>contact material:</b>	contact pin: brass contact spring: copper - beryllium
<b>contact surface material:</b>	nickel
<b>housing material:</b>	PA
<b>environmental conditions:</b>	
<b>temperature range:</b>	-15 °C to +70 °C
<b>flammable class:</b>	
<b>housing (basic material):</b>	UL 94 V - 2
<b>drawing</b>	