


Product Area Female cable connector, metal locking system, screw termination
M12 connectors A-Coding serie 713

Pole 8
Article number 99 0486 12 08

illustration



scale drawing



Contact Arrangement



	X	Y
1	-2,69	0,57
2	-0,57	2,69
3	1,66	2,20
4	2,75	0,19
5	1,94	-1,94
6	-0,19	-2,75
7	-2,20	-1,66
8	0,00	0,00

You can find the item description and assembly instruction on the next page.

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	Screw
Termination	screw
Wire gauge (mm)	0,50 mm ²
Wire gauge (AWG)	20
Cable outlet	6 - 8 mm
Upper temperature	+85 °C
Lower temperature	-40 °C

Material

Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PA
Material of housing	PA

Cable data

Contacts 8: cable outlet: 6-8 mm, Female cable connector, metal locking system, screw termination

Electrical values


Rated voltage	60 V
Rated impulse voltage	800
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	2 A
Volume resistivity	≤ 3 mΩ
EMV compliance	-
Degree of protection	IP 67
Mechanical operation	> 50 mating cycles




Product Area Female cable connector, metal locking system, screw termination
M12 connectors A-Coding serie 713

Pole 8
Article number 99 0486 12 08

Item description



Installation instructions / Mounting cutout



	Schraubklemmversion screw connection	Lötversion solder version	Käfigzugfederversion wire clamp connection
Maß A/mm measure A/mm	5	3,5	7