



针位排布图
 Contact arrangement



技术参数:

- 产品系列: M12 D-Code
- 插针数: 4
- 额定电流(40°C): 4A
- 额定电压: 250V
- 额定脉冲电压: 2500V
- 污染等级: 3
- 接触电阻: ≤10mΩ
- 防护等级: IP67
- 插拔次数: >100
- 温度范围: -40°C...+85°C
- 绝缘阻抗: ≥100MΩ
- 接线方式: 冷压压接
- 线径范围: max.0.82mm² (max.AWG18)
- 电缆直径: 6-8mm
- 电缆剥线长度: 30mm
- 导线剥线长度: 4mm

材料特性:

- 锁紧螺帽: 金属
- 插针材料: 铜合金
- 插针表面处理: 镀金
- 外壳材料: 锌合金
- 绝缘材料: PA

Technical specification:

- Series: M12 D-Code
- Number of contacts: 4
- Rated current(40°C): 4A
- Rated voltage: 250V
- Rated impulse voltage: 2500V
- Pollution degree: 3
- Contact resistance: ≤10mΩ
- Degree of protectio: IP67
- Mating cycles: >100
- Temperature range: -40°C - +85°C
- Insulation resistance: ≥100MΩ
- Termination method: Crimp termination
- Wire gauge: max.0.82mm² (max.AWG18)
- Cable Outlet: 6-8mm
- Stripping length of the sheath: 30mm
- Stripping length of the individual wire:4mm

Material properties :

- Material of locking system: Metal
- Material of contact: copper alloy
- Contact plating: Au
- Material of housing : Zinc die-cast
- Material of Insert: PA

Standards: IEC 61076-2-101

符合标准: IEC 61076-2-101

						表面处理 Finish	-				图号 Drawing No.	-
						材料 Material	-				产品代号 Part Code	M12-MC04D-T-D8-SH
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	1630040102002
绘图 Drawn	TC CHEN	姓名/Name	日期/Date	标准化 Stand.	-	-	1:1	V1.0	55.1g	-	产品名称 Part Name	-
审核 Checked	ZM LIN	姓名/Name	日期/Date									
工艺 Process	-	批准 Approved	YY LUO	日期/Date	18.02.2017			All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		