

i2000 flex AC Current Clamp

Electrical specifications	
Current ranges	20 A 200 A 200 A AC rms
Output sensitivity (AC-coupled)	100 mV 10 mV 1 mV 1 mV per A
Load impedance	100 kΩ minimum
Accuracy	at +25 °C ± 1 % of range (45 Hz to 65 Hz)
Linearity	10 % to 100 % of range ± 0.2 % of reading
Noise	8 mV ac rms (30 A) 2 mV ac rms (300 A, 3000 A)
Frequency range	10 Hz to 20 kHz (-3 dB)
Phase error	< ± 1 ° (45 Hz to 65 Hz) ± 10 ° (at 20 kHz)
Position sensitivity	with cable > 25 mm from the coupling ± 2 % of range
External field	with cable > 200 mm from the head ± 1 % of range
Power supply	2 x AA/MN 1500/LR6 Alkaline, 200 hours, low battery indicator
Temperature Coefficient	± 0.08% of reading per °C
Working voltage	see Safety standards section 600 V AC rms or DC

General Specifications	
Head Circumference	610 mm (24 in)
Head cable diameter	14.3 mm (0.56 in)
Head bend radius	38.1 mm (1.5 in)
Cable length (head to electronics)	2 m (6.56 ft)
Output connection	Molded 4 mm safety plugs (not integrated)
Operating temperature range	0 °C to +70 °C (32 °F to 158 °F) (head and electronics)
Storage temperature range	-40 °C to +105 °C (-40 °F to 221 °F) (head) -20 °C to +85 °C (-4 °F to 185 °F) (electronics)
Operating humidity	15 % to 85 % (non-condensing)
Weight	180 g (6.34 oz) (head) 190 g (6.70 oz) (electronics)
Safety standards	EN 61010-1: 2001 EN 61010-2-032: 2002 EN 61010-031: 2002 600 Vrms, Category III, Pollution Degree 2 Use of the probe on uninsulated conductors is limited to 600 V ac rms or dc and frequencies below 1 kHz.
EMC standards	EN 61326: 1998 +A1, A2, & A3
Dimensions	HxWxD 116 mm x 68.5 mm x 30 mm (4.56 in x 2.69 in x 1.18 in)