

DHI-LM22-A200X

21.5" FHD Monitor



Features:

- · Light and cost-effective plastic housing;
- · Ultra-narrow bezel ,elegant appearance, Metal base;
- \cdot 178°H/178°V extra-wide viewing angle for overall viewing performance;
- · High fidelity digital processing for a brilliant and vivid video;
- · Support multiple signal inputs such as HDMI, VGA; AUDIO
- · Physical button control mode;
- · Low energy consumption, long service life;
- · Anti-blue light design, eye-protective.















Technical Specification

| . 1 | 1 | ٦ | ^ | ı |
|-----|---|---|---|---|
| | | | | |

| Model | DHI-LM22-A200X | |
|----------------------|------------------------|--|
| | | |
| Display | | |
| Screen Size | 21.5" | |
| Panel type | VA | |
| Aspect Ratio | 16:9 | |
| Resolution | 1920x1080(FHD) | |
| Backlight | WLED | |
| Brightness/Luminance | 250 cd/m²(max) | |
| Contrast | 3000:1 | |
| Display Color | 16.7M(8bit) | |
| Viewing Angle(H/V) | 178°(H)/178°(V) | |
| Response time | OD 7ms | |
| Refresh Rate | 100Hz (max) | |
| Signals | | |
| Input | VGA×1, HDMI×1, Audiox1 | |
| Output | NO | |
| Speaker | | |
| Speaker | 2Wx2 | |

General

| Power Supply | DC 12V | | |
|------------------------------|-------------------------|-----------------------|--|
| Consumption (Standard) | 30W | | |
| Consumption (Standby) | ≤0.5W | | |
| Net Weight | 2.00kg | | |
| Gross Weight | 2.80kg | | |
| Bezel Width | 2mm | | |
| Wall Mount | VESA 75*75mm | | |
| Dimension with stand (W×H×D) | 491*174*380mm | | |
| Package(W×H×D) | 550*102*348mm | | |
| Work Environment | Temperature | 0°C~40°C (32°F~104°F) | |
| WORK ENVIRONMENT | Humidity | 20%~90% | |
| Accessory | | | |
| Standard | HDMI cable,Adapter,base | | |
| Certifications | | | |
| | | | |

South Africa Approved NRCS LOA

Rev 002.000

The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.

Certifications