

90w POE injector

POE Injector support
“IEEE 802.3af/at/bt” "POE++" POE supply

Main Features

- 2 port Gigabit Rj45 network, 1GE POE out+1GE data input
- Support Spherical camera, Industrial wireless AP etc.
- Fluid Control: Full-duplex: IEEE 802.3x, Half-duplex: back pressure.
- Auto MDI/MDIX.
- Support port lightning protection.
- Store-and-forward.
- All ports support wire speed switch, jumbo frame transmission.
- Plug and play, self-adaption.

Specifcation

Power pin	12+/45+ 36-/78-
POE out	55V 1.63A
Power	90W
POE	IEEE802.3af/at/bt POE++
Data pin	12364578
Power input	AC 100-240V 50/60HZ
Shell	Metal case
Port	1GE POE output+1GE data input
Function	Plug and Play, without configuration management Under-voltage, over-voltage, over current short circuit protection System Reliability: MTBF>100k hours Comply to EN55022, CLASS BCE & RE
Environment	Working Temperature: 0°C~40°C Storage temperature: -40°C~80°C Working Humidity: 10%~90% RH non-condensing Storage Humidity: 5%~90% RH non-condensing
Speed	Ethernet 10Mbps half-duplex, 20Mbps full-duplex Fast Ethernet 100Mbps half-duplex, 200Mbps full-duplex Gigabit Ethernet 2000Mbps full-duplex
Network Media	10Base-T: Pair 2 Category 3(cat 3) and above UTP/STP(≤150m) 100Base-TX: Pair 2 Category 5(cat 5) and above UTP/STP(≤150m) 1000Base-T: Pair 4 Category 5(Cat5e) and above UTP/STP(≤150m)
ProductSize	182mm*72mm*39mm(L*W*H)
Weight	0.9 Kg

Product Information

Product Details: 1GE POE out+1GE data input