



MINIWATT/S

Sirena elettromeccanica piccola |
Small electromechanical siren



Dimensioni ridottissime, eccezionale resa acustica e minimo consumo sono le caratteristiche principale delle sirene serie Miniwatt.

Indispensabili ovunque si richiedano eccellenti e sicure prestazioni sonore ed l'eventualità di dover nascondere la sirena.

Trovano ideale applicazione in impianti antifurto, quadri di comando, segnali di emergenza in generale. La versione con staffa è adatta ad installazioni a parete.



Small size, exceptional acoustic performance and minimum power consumption are the main features of the sirens Miniwatt. Indispensable wherever they require excellent sonic performance and secure and the possibility of having to hide the siren. Finds its ideal application in alarm systems, control panels, emergency signals in general. The version with bracket is suitable for wall mounting

GENERALI | GENERAL FEATURES

Modello	Model	Miniwatt / S 12v ac/dc	Miniwatt / S 24V ac/dc
Codice	Part Number	14.42.005C	14.43.004C
Servizio	Service	15 min	15 min

SUONO | SIREN

Livello	Level	98dB@1m	103dB@1m
Tipo	Type	Continuo / Continuous	
Frequenza	Frequency	1000Hz	1500Hz

ALIMENTAZIONE | POWER SUPPLY

Tensione nominale	Voltage Rating	12V	24V
Potenza nominale	Rated	10W	10W
Frequenza	Frequency	dc - 60Hz	dc - 60Hz
Corrente media	Average Current	0.83A	0.41A
Classe isolamento	Isolation Class	E	E

MECCANICHE | MECHANICAL

Materiali costruttivi	Building materials	ABS
Peso	Weight	170g
Ingombro massimo	Maximum Size	87x79mm

AMBIENTE | ENVIRONMENT

Temperatura esercizio	Operating Temperature	-20 ÷ 40°C
Grado IP motore	Engine IP Degree	44
Grado IP sirena	Fan IP degree	14

OMOLOGAZIONI | APPROVAL

Europa	Europe	CE
--------	--------	----