

TBM807 Electricians DMM (True RMS)

- Temperature
- Splash proof
- Beep guard
- Diode
- Continuity
- Data hold
- Min/max
- Relative zero
- Back-lighted display



Technical Specification

AC/DC Voltage	400m, 4, 40, 400, 1000V
AC/DC Current	400 μ , 4000 μ , 40m, 400m, 4, 10A
Resistance	400, 4K, 40K, 400K, 4M, 40M Ω
Frequency	50, 500, 5K, 50K, 500K, 1MHz
Temperature	-20°C to 300°C
Capacitance	500n, 5 μ , 50 μ , 500 μ , 3000 μ F
Accuracy	
DC Voltage	$\pm 1,0\%$ + 4 Digit
AC Voltage	4 - 400V $\pm 1,5\%$ + 5 Digit 1000V $\pm 4,0\%$ + 5 Digit
DC Current	$\pm 1,2\%$ + 3 Digit
AC Current	$\pm 1,8\%$ + 4 Digit
Resistance	$\pm 2,0\%$ + 4 Digit
Frequency	$\pm 0,5\%$ + 4 Digit
Temperature	$\pm 2,0\%$ + 3°C
Capacitance	$\pm 3,5\%$ + 6 Digit
Protection	
AC/DC Voltage	1050Vrms, 1450V PEAK
AC/DC Current	0,5 A/250V FUSED 15A /250V FUSED
Resistance	600V DC/AC RMS
Input Warning	✓
Transient	6.5KV LIGHTNING SURGE
Protection	(1.2/50 μ s)



Model Specification

Accessories	Temp Probe
Dimensions (mm)	198(L) x 97(W) x 55(H)
Power Source	2 x 1.5V AAA Batteries
Weight	396g