


Product information

VAD 1A-1-3-M12-5

Industrial Connecting Solutions:Cables and Adapters:T-connectors / adaptors:M8, M12, valve plug - T-connectors/adaptors:M12 - Vxx:M12 Valve adaptor according to DIN EN 175301-803, form A:VAD 1A-1-3-M12-5

<https://www.e-catalog.beldensolutions.com:443/link/57078-24228-256254-57229-218892-219413-219626-219628/en/conf/ui/istate>


Name	VAD 1A-1-3-M12-5
	
	Valve adaptor according to DIN EN 175301-803, form A, with LED function indicator, varistor voltage protection, connected protective earth, with M12 male receptacle connector, 2 poles + PE
Delivery informations	
Availability	available
Product description	
Type	VAD 1A-1-3-M12-5
Order No.	12141
Description	Valve adaptor according to DIN EN 175301-803, form A, with LED function indicator, varistor voltage protection, connected protective earth, with M12 male receptacle connector, 2 poles + PE
Color of housing	black translucent
Product characteristics	Vibration resistance, Oil resistance
Classification	
Belden brand	Lumberg-Automation
Environmental conditions	
Environmental temperature	-25 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Housing material / Molded body, side 2	CuZn, nickel-plated
Contact bearer material	PBT
Contact bearer material, side 2	PA
Contact material	CuZn
Contact material, side 2	CuZn
Contact material - Surface refinement	pre-nickeled and tin-plated
Contact material - Surface refinement, side 2	pre-nickeled and 0.8 microns gold-plated
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current I_n	4 A at 40 °C
Nominal voltage	24 V
Rated voltage	32 V
Insulation resistance	> 1 GΩ
Varistor data	
Nominal voltage (Varistor)	47 V at 0.1 mA
Typ. limiting voltage (Varistor)	110 V at 5 A
Max. pulse energy (Varistor) (standard impulse 10/1000us)	0,9 Ws
Max. continuous power loss (Varistor)	0,01 W
Scope of delivery and accessories	
Scope of delivery	Screw (fitted)

Industrial Connecting Solutions:Cables and Adapters:T-connectors / adaptors:M8, M12, valve plug - T-connectors/adaptors:M12 - Vxx:M12 Valve adaptor according to DIN EN 175301-803, form A:VAD 1A-1-3-M12-5

<https://www.e-catalog.beldensolutions.com:443/link/57078-24228-256254-57229-218892-219413-219626-219628/en/conf/ulistate>

Picture

Drawing



*a M3-Schraube
M3 screw

Belden Deutschland GmbH
Im Gewerbepark 2
58579 Schalksmühle
Germany
Phone: +49 7127/14-1806
E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.