

T835 DIY DMM

- Low Cost
- Temperature
- Continuity
- Diode
- Data Hold



Technical Specification

| | |
|-------------------|------------------------|
| DC Voltage | 200,2,20,200,600V |
| AC Voltage | 200,600V |
| DC Current | 200µ,2m,20m,200m,10A |
| Resistance | 200,2K,20K,200K,20MΩ |
| Temperature | -20°C to 750°C |
| Accuracy | |
| DC Voltage | ± 0.5% + 2 Digit |
| AC Voltage | ± 1.2% + 10 Digit |
| DC Current | ± 1.5% + 2 Digit |
| Resistance | ± 0.8% + 2 Digit |
| Temperature | ± 1% + 3 Digit |
| Protection | |
| DC Voltage | 600V DC / 600V AC RMS |
| AC Voltage | 600V DC / 600V AC RMS |
| DC Current | 0.25A 250V 10A UNFUSED |
| Resistance | 500V DC / 500V AC RMS |
| Thermocouple | -20°C to 200°C |
| Fuse | 250mA 250V (20x5)mm |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | K-type Thermocouple |
| Dimensions (mm) | 138(L) x 72(W) x 38(H) |
| Power Source | 9V Battery |
| Weight | 153g |

T1300H Electronic DMM

- Low Cost
- Transistor
- Diode
- Continuity



Technical Specification

| | |
|-------------------|---|
| DC Voltage | 200m,2,20,200,600V |
| AC Voltage | 200,600V |
| DC Current | 200µ,2m,20M,200M,10A |
| Resistance | 200,2K,20K,200K,2000MΩ |
| Accuracy | |
| DC Voltage | ±0,5% + 1 Digit |
| AC Voltage | ±1,2% + 10 Digit |
| DC Current | 200µ-200mA ±1,2%+2 Dig 10a ±2,0% + 5 Dig |
| Resistance | ±0,8% + 5 Digit |
| Diode | ±2,8V |
| Protection | |
| AC/DC Voltage | 600V DC/AC RMS |
| AC/DC Current | 200mA /250V FUSED |
| Resistance | 250V DC/AC RMS <10 sec. |
| Fuse | 250mA 250V (20x5)mm |

Model Specification

| | |
|-----------------|------------------------|
| Dimensions (mm) | 138(L) x 72(W) x 38(H) |
| Power Source | 9V Battery |
| Weight | 135g |

T2400TH Hobbyist DMM

- Low cost
- Temperature
- Diode test
- Continuity



Technical Specification

| | |
|-------------------|--|
| DC Voltage | 200m,2,20,200,600V |
| AC Voltage | 200,600V |
| Resistance | 200,2K,20K,200K,20MΩ |
| DC Current | 200µ,2m, 20m, 200m,10A |
| Temperature | -20°C to 750°C K-type 0°C to 40°C Built in sensor |
| Continuity | Buzzer sounds below 20Ω |
| Diode | 2,8 V max |
| Accuracy | |
| DC Voltage | ±0,5% + 1 Digit |
| AC Voltage | ±1,2% + 10 Digit |
| Resistance | ±0,8% + 3 Digit |
| DC Current | ±1,2% + 2 Digit |
| Temperature | -20°C to 16°C 401 to 750°C ± 2,5% 17 to 400°C ± 1% (400°C to 1000°C) 1,5% + 10°C |
| Built in Sensor | (0°C to 40°C) ±2°C |
| Protection | |
| DC Voltage | 600V DC/AC RMS |
| AC Voltage | 600V DC/AC RMS |
| Resistance | 250V DC/AC RMS |
| Fuse | 250mA 250 (20x5)mm |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | Temp Bead Probe |
| Dimensions (mm) | 138(L) x 72(W) x 38(H) |
| Power Source | 9V Battery |
| Weight | 153g |

T1504 Auto Ranging DMM

- Low cost
- Continuity
- Diode
- Capacitance
- Frequency
- Data hold
- Temperature



Technical Specification

| | |
|-------------------|---|
| DC voltage | 400m,4,40,400,600v |
| AC voltage | 4,40,400,600v |
| AC/DC current | 400µ,400k,40m,200m,10a |
| Resistance | 400,4k,40k,400k,4m,20mΩ |
| Frequency | 10,100,1K,10K,100K, 1M,5MHZ |
| Capacitance | 4n,40n,400n,4µ,40µ,100µF |
| Accuracy | |
| DC Voltage | ±0,5% + 3 Digit |
| AC Voltage | ±0,8% + 3 Digit |
| DC Current | ±1,2% + 5 Digit |
| AC Current | ±1,5% + 5 Digit |
| Resistance | ±1,2% + 2 Digit |
| Frequency | ±1,0% + 5 Digit Vpp 600mV |
| Capacitance | ±3,0% + 5 Digit |
| Temperature | -20°C to 750°C -20° to 400°C ± 1.0% 401 To 750°C ± 3.0% |
| Protection | |
| AC/DC Voltage | 600V DC/AC RMS |
| AC/DC Current | 400mA FUSED 10A 15 sec. FUSED |
| Resistance | 250VDC/AC RMS <30 sec. |
| Capacitance | 250VDC/AC RMS <30 sec. |
| Frequency | 600V dc/ac RMS <30 sec. |
| Fuse | 250mA 250v (20x5)mm |

Model Specification

| | |
|-----------------|------------------------|
| Accessories | Temp Bead Probe |
| Dimensions (mm) | 138(L) x 72(W) x 38(H) |
| Power Source | 2 x 1.5v AAA Batteries |
| Weight | 153g |