




**Model Name**

**32LF89**



|                               |                           |
|-------------------------------|---------------------------|
| Size                          | 31.51" diagonal           |
| Backlight                     | DLED direct Type          |
| Maximum resolution            | 1366×768                  |
| Contrast ratio (Typ)          | 3000:01:00                |
| Response time(Typ)            | 6.5ms                     |
| Display scale                 | 16:09                     |
| Viewing angle(CR>10)          | Typ(H:178°,V:178°)        |
| Display Colors                | 16.7 M                    |
| Color Gamut(NTSC)             | ≥ NTSC 58%                |
| LCM Center Luminance of White | Min:180cd/m2;Typ:200cd/m2 |
| Local dimming                 | nonsupport                |
| Uniformity of Luminance       | ≥60%                      |

## 2.Hardware Information

|                     |       |
|---------------------|-------|
| Audio power(Output) | 6W+6W |
| HDMI 1.4 (HDCP 1.4) | 2     |
| USB 2.0             | 2     |
| VGA                 | -     |
| AV In               | 1     |
| Audio Out           | 1     |

## 3.Software Function

|                          |       |
|--------------------------|-------|
| Channel list             | YES   |
| Channel edit             | YES   |
| Picture freezing         | NO    |
| MTS/NICAM                | NICAM |
| Sleep time setting       | YES   |
| Teletext                 | NO    |
| PVR                      | NO    |
| EPG                      | NO    |
| V_CHIP/Parental Guidance | NO    |
| CC(Closed caption)       | NO    |
| AD(Audio description)    | NO    |
| TTS(Text to Speech)      | NO    |
| CI+                      | NO    |
| DOLBY                    | NO    |
| HDMI-ARC                 | YES   |

|                                                      |                                                                    |
|------------------------------------------------------|--------------------------------------------------------------------|
| HDMI-CEC                                             | YES                                                                |
| HDMI-MHL                                             | NO                                                                 |
| Operation system                                     | LINUX                                                              |
| OTA                                                  | NO                                                                 |
| Hotel mode                                           | NO                                                                 |
| <b>4.Structure Information</b>                       |                                                                    |
| Size (without stand) L×W×H                           | 716x58x423mm                                                       |
| Size (with stand) L×W×H                              | 716x198x478mm                                                      |
| Size (carton) L×W×H                                  | 751x74x458mm                                                       |
| Net Weight (without stand)                           | 3.15kg                                                             |
| Net Weight (with stand)                              | 3.21kg                                                             |
| Gross Weight (without stand)                         | 3.98kg                                                             |
| Gross Weight (with stand)                            | 4.04kg                                                             |
| Size (Wall hanging)                                  | 100x100mm                                                          |
| <b>5.Power Management&amp;Safety&amp;Certificate</b> |                                                                    |
| Power input                                          | 100-240VAc                                                         |
| Fire rating                                          | UL94-HB75                                                          |
| Standby power                                        | ≤0.5W                                                              |
| Rated power                                          | 55W                                                                |
| Working condition                                    | Temperature : 5℃～40℃ humidity : 20～80□ atmosphere : 86KPa～106KPa   |
| Storage condition                                    | Temperature : -20℃～55℃ humidity : 20～80□ atmosphere : 86kPa～106kPa |
| <b>6.Accessory</b>                                   |                                                                    |
| Stand(Optional)                                      | 1PCS                                                               |
| Remote control                                       | 1PCS                                                               |
| Instruction                                          | 1PCS                                                               |
| Warranty card(Optional)                              | 1PCS                                                               |
| Battery(Optional)                                    | 2PCS                                                               |