

**datasheet for SEB 2610 F4,8**  
**article number: 972355100**

<b>product description:</b>	<b>order number: 972 355-100</b>
<b>description:</b>	Safety built-in socket, 4 mm diameter, contact-protected, with 4.8 x 0.8 tab connector complying with DIN 46 244, gold-plated brass. For installation into switchpanels and equipment chassis with wall thicknesses up to 6 mm. Installation hole: 12.2 mm diameter, Tightening torque: 50 Ncm, Accessory: assembly tool MW SEB
<b>typ:</b>	SEB 2610 F4,8 schwarz/black
<b>system:</b>	4mm safety system
<b>order number:</b>	972 355-100
<b>color</b>	
<b>other color versions:</b>	
<b>technical data</b>	
<b>measurement category acc. to IEC 61010:</b>	CAT III
<b>type of contact:</b>	4 mm socket (unsprung)
<b>type of termination:</b>	flat connector 4.8 x 0.8 mm
<b>rated voltage:</b>	AC/DC 1000 V
<b>rated current:</b> <a href="#">Please consider derating curve!</a>	25 A
<b>contact resistance:</b>	5 mOhm
<b>mounting:</b>	screw
<b>material</b>	
<b>contact material:</b>	brass
<b>contact surface material:</b>	gold
<b>housing material:</b>	PA
<b>environmental conditions:</b>	
<b>temperature range:</b>	-40 °C to +80 °C
<b>flammable class:</b>	
<b>housing (basic material):</b>	UL 94 V - 2
<b>drawing</b>	