

BLADE HOOK HB(E)	DISCONNECT			FULLY INSULATED DISCONNECT		T-SPLICE (TS)	QUICK SPLICE (QS)	CLOSED END CONNECTORS (CE)
	MALE DM(E)	FEMALE DFE)	PIGGY-BACK PB(E)	MALE (F-DM)	FEMALE (F-DF)			
<b>(T) 1HB</b> (4,6mm)	<b>(T) 1DM</b> (6,4mm)	<b>(T) 1DF</b> (6,4mm)			<b>TF1DF</b> (6,4mm)			
<b>1 HB3</b> (3mm)	<b>(T) 1DM4</b> (4,8mm)	<b>(T) 1DF4</b> (4,8mm)	<b>(T) 1PB</b> (6,4mm)		<b>TF1DF4</b> (4,8mm)	<b>1TSRD</b>	<b>1QS</b>	<b>CE1</b>
	<b>(T) 1DM2</b> (2,8mm)	<b>(T) 1DF2</b> (2,8mm)			<b>TF1DF2</b> (2,8mm)			
				<b>F1DMY</b> (6,4mm Nylon)	<b>F1DFY</b> (6,4mm Nylon)			
<b>2HB</b> (4,6mm)	<b>(T) 2DM</b> (6,4mm)	<b>(T) 2DF</b> (6,4mm)	<b>(T) 2PB</b> (6,4mm)		<b>TF2DF</b> (6,4mm)	<b>2TSBL</b>	<b>2QS</b>	<b>CE2</b>
<b>2HB3</b> (3mm)	<b>(T) 2DM4</b> (4,8mm)	<b>(T) 2 DF4</b> (4,8mm)		<b>F2DMY</b> (6,4mm Nylon)	<b>F2DFY</b> (6,4mm Nylon)			
		<b>(T) 2DF9</b> (9,4mm)			<b>TF2DF4</b> (4,8mm)			
<b>3HB</b> (4,6mm)	<b>(T) 3DM</b> (6,4mm)	<b>(T) 3DF</b> (6,4mm)	<b>(T) 3PB</b> (6,4mm)		<b>TF2DF</b> (6,4mm)	<b>1TSYL</b>	<b>3QS</b>	<b>CE5</b>
<b>3HB3</b> (3mm)		<b>(T) 3DF9</b> (9,4mm)		<b>F3DMY</b> (6,4mm Nylon)	<b>F3DFY</b> (6,4mm Nylon)			

● 0,25 - 1,65mm<sup>2</sup> - 19Amp 600V ● 1,04 - 2,63mm<sup>2</sup> - 27Amp 600V ● 2,63 - 6,64mm<sup>2</sup> - 48Amp 600V  
 NOTE: 1) For inner copper tube (Twingrip) use prefix (T). 2) ‡(A) Option Narrower.