

UT343D

Coating Thickness Gauge

UT343D coating thickness gauge can measure coating thickness of ferrous and non-ferrous materials. This device is designed with a unique quick test feature, which allows users to set thickness range and using a 3-color LED and audio alarm to display test results, greatly increasing work efficiency. UT343D display is also auto rotatable. This CE certified device can store up to 500 sets of data for further analysis through the PC analytical software.

- LCD brightness control
- Auto rotatable screen
- Unit conversion
- Audio alarm
- LED alarm
- PC analysis software
- USB communication
- Quick test mode
- Auto power off
- Low battery indication



SPECIFICATION	Range
Certificates	CE, RoHS
Measurement range	0-1250um
Accuracy	±(3%+1)um
Resolution	0.1um (0-99.9um); 1um (100-1250um)
Measurement method	Single/continuous
Measurement mode	MAX/MIN/AVG
Metal type	Ferrous/ non-ferrous
Display type	2-inches TFT LCD (320 x 240 pixels)
Data storage	500 groups
GENERAL CHARACTERISTICS	
Power	3V battery (R03) x 2
Display	48mm x 36mm
Product net weight	175g
Product size	153.5mm x 64.5mm x 41mm
Standard accessories	Micro USB interface cable, calibration pieces, batteries, English manual
Standard individual packing	Gift box, cloth bag
Standard quantity per carton	10pcs
Standard carton measurement	450mm x 325mm x 255mm
Standard carton gross weight	5.9kg



- Auto-rotatable screen: 0°, 90°, 180°, 270°

- Quick test mode