

### T475 Volt/Current Tracer

- Detect current through shielded/armoured cable
- Adjustable sensitivity



#### Technical Specification

Detection	Non Contact
Indication	Visual & Audio
Sensitivity	Adjustable
Voltage Detection	5V ~1000V AC
Current Sensitivity	>100mA
Frequency Range	50 to 500Hz
Operating Temp	-10°C ~50°C
Operating Humidity	<80 %RH

#### Model Specification

Dimensions (mm)	192(L) x 31(W) x 24(H)
Power Source	4 x 1,5V LR44 Batteries (T515BATT)
Weight	60g

### T180 Tone and Probe Kit

- Complete with tone generator and amplifier probe
- Recessed On/Off button
- Sensitivity control
- Alligator clips and RJ11 connector
- Single or dual alternating tone
- Use on de-energised circuits



Meter Supplied With Certificate of Conformance

#### Technical Specification

Tone Generator	Waveform	Square Wave
	Frequency	±1.13kHz
	Amplitude	9V P-P
	Over voltage Protection	±100V
	Single Tone	✓
Amplifier Probe	Alternating Tone	✓
	Frequency Detection	1-12kHz
	Receiver distance	50-60cm
	Sensitivity Control	✓

#### Model Specification

Optional Accessories	Carry pouch
Dimensions (mm)	Probe 270(L) x 56(W) x 25(H) Tone 62(L) x 58(W) x 34(H)
Power Source	Probe 9V Battery Tone 9V Battery
Weight	250g/Set

### SOLDEGAS

- Highest quality butane
- 300ml
- Ultra refined for maximum care & performance



### T77 Laser Chalk Line

- Vertical line
- Horizontal line
- Cross line
- Auto-levelling
- Hanging clip



### T33 Switchable Oscilloscope Probes

- 60MHz
- Switchable x1x10



### TMS68 Metal, Lazer Line, Microwave Detector

- Lazer line with spirit level
- Metal detector
- Continuity
- Microwave detection
- Polarity check
- Torch function
- LED indication

