

> Overnight Chargers

Standard battery chargers and are ideal for regular household or office use. Some are used for overnight business trips and travel. Some are also powered by USB ports.

Camelion®

BC-1001A

BC-1001B

Charges:

1-2 x AA

1-2 x AAA

1 x 9V

Ni-MH

Ni-Cd



SPECIFICATIONS

Input: AC 100-240V ~ 50/60Hz

Output: DC 2 x (1.4V \approx 200mA) AA/AAA Size

DC 1 x (9V \approx 25mA) 9V Size (BC1001A)

DC 1 x (9V \approx 16mA) 9V Size (BC1001B)

MAIN FEATURES

- 3 Independent Charging Channels
- 12 Hours Timer Control (BC1001A)
- Reverse Polarity Protection
- Slim and Portable
- Built-in Switching Adaptor for Worldwide Use

- LED Indicators (BC-1001A)

Red	Charging
Off	Fully charged

- LED Indicators (BC-1001B)

Red	Charging or charge complete
-----	-----------------------------

CHARGING TIMES

Type of Battery	Charging Times (Appr.)	
	BC-1001A	BC-1001B
Ni-MH AA 2700mAh	12.0	14.7
Ni-MH AA 2000mAh	12.0 h	12.0 h
Ni-MH AA 1500mAh	9.0 h	9.0 h
Ni-MH AAA 800mAh	4.8 h	4.8 h
Ni-MH 9V 200mAh	9.6 h	15 h
Ni-Cd AA 1000mAh	6.0 h	6.0 h
Ni-Cd AAA 300mAh	1.8 h	1.8 h

AVAILABLE COLORS

 Black  Titanium

PACKAGING



Blister		
Plug:	TUV	UL
Weight(g)	62	55
Dimensions (W) x (H) x (D) (mm)	87 x 172 x 50	87 x 172 x 50
Inner Carton		
Packs / Inner ctn	32	32
Net Weight(kg)	1.98	1.76
Gross Weight(kg)	2.42	2.2
Dimensions (L) x (W) x (H) (cm)	39.5 x 37.5 x 18	39.5 x 37.5 x 18
Outer Carton		
Packs / Carton	64	64
Net Weight(kg)	4.0	3.52
Gross Weight(kg)	7.5	6.8
Dimensions (L) x (W) x (H) (cm)	41 x 39 x 39	41 x 39 x 39
Volume(cbm)	0.0624	0.0624