

### Product Features

- Ultra-reliable Lithium Iron Phosphate (LiFePO4) technology
- Integrated battery management System (BMS)
- Light weight & compact
- Water & dust resistant (IP56)
- Highly durable ABS enclosure
- Compatible with leading 24V inverters & chargers



### Technical Specifications

GENERAL INFORMATION	
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Usable Capacity	2808 Wh @C10, 25°C
Nominal Voltage	26 VDC
Operating Voltage Range	23.2 VDC – 28.4 VDC
Operating Temperature Range	Charge: 0°C ~ 45°C   Discharge: -20°C ~ 55°C
Cycle Life @ 100% DoD	> 2000 cycles (2800 Wh @C10, 25°C)
Cycle Life @ 80% DoD	> 3000 cycles (2240 Wh @C10, 25°C)
Cycle Life @ 50% DoD	> 5000 cycles (1400 Wh @C10, 25°C)
Dimensions (mm)	522 x 239 x 221mm (W x D x H)
Weight (kg)	25.6 kg
Warranty Period	3 Years
Terminal	M8 (female)

CHARGE / DISCHARGE	
Bulk Voltage	28.4 – 28.8VDC
Float Voltage	27.6 VDC
Discharge Voltage (min.)	23.2 V
Charge Current (max.)	Recommended: 20A   Maximum: 100A continuous
Discharge Current (max.)	Recommended: 20A   Maximum: 100A continuous   Peak: 200A (<5 seconds)
Self-discharge Rate	< 3% per month
Charge & Discharge Efficiency	96% - 99% @C1

PROTECTION	
Environmental Protection	IP56
Over-current Protection	100 A
Over-voltage Cut-out	31.2 V
Under-voltage Cut-out	20.0 V