

DVR XY9108H

8CH 960H Network

Digital Video Recorder



FEATURES

- ➔ Use the standard H.264 video compression format stream lower,high quality,longer recording time, taking up less bandwidth resources
- ➔ GUI OSD interface,USB Mouse controller,more intuitive,easier to use for user-friendly
- ➔ With cloud access technology (our cloud service address www.dvrcenter.net) you can do remote view by one step without any complicated port forwarding. **(P2P)**
- ➔ 8CH 960H (96fps) or 8CH D1 realtime recording.
- ➔ Dual-stream design,network remote view effects and local recording effects parameters can be set separately,independently of each other.
- ➔ Hexaplex operation simultaneously:Preview,recording,playback,backup,network live,mobile phone view
- ➔ Multiple record mode:Auto、timer、 motion recording mode
- ➔ Recording playback support:Normal play、 Speed play、 Fast back play、 Manual single-frame slow play
- ➔ Support drag the progress bar can be targeted playback time directly
- ➔ Support 4CH 960H (80fps) playback simultaneously, each channel can be enlarge to full screen
- ➔ Support Network function:one IE browser centralized monitoring and CMS Software for multiple DVR
- ➔ Support 3G, WIFI, DHCP, DDNS, PPPoE、 NTP and UPNP network service.
- ➔ Support remote surveillance up to 10 users simultaneously via the Enternet Explorer web browser
- ➔ Support more than 17 kinds protocol of the PTZ control
- ➔ Supports Multiple backup mode: USB flash drive,USB hard disk and network backup
- ➔ Support pre-alarm recording (before 10 sec),not lose any suspicious screen
- ➔ Support Mobile phone remote view by Symbian;Windows Mobile;Android system;Iphone;Blackberry
- ➔ Support High-Definition VGA output(VGA and BNC can work at the same time) and HDMI
- ➔ System auto recovery to power after power reconnected,and return to the pre-power-down state



Video System	NTSC / PAL
Video Compression Format	H.264
GUI OSD	YES
Video Input(BNC)	8CH BNC input (composite video signal 1 Vp-p 75Ω BNC)
Video Output(BNC)	1CH BNC output
Audio Input/Output	4CH RCA input, 1CH RCA output
Maximum Recording Rate	960H:960×480 pixels with 20 FPS <NTSC> /960×576 pixels with 20 FPS<PAL> D1:704×480 pixels with 30 FPS <NTSC> /704×576 pixels with 25 FPS<PAL> HD1:704×240 pixels with 30 FPS <NTSC> /704×288 pixels with 25 FPS<PAL> CIF:352×240 pixels with 30 FPS <NTSC> /352×288 pixels with 25 FPS<PAL>
Image Quality Setting	Supper Best,Well,Good,Medium,Normal and Bad
Hard Disk Storage	Support 1 SATA HDD, max capacity is 2TB/pcS
Alarm Input/Output	2CH alarm input,1CH alarm output
Multiplex Operation	Live display/record/playback/backup/network transmit
Recording Mode	Manual/Timer/Motion/Alarm
Playback Mode	Multiple slow and rapid play speeds,manual and single-frame play
Backup Device	USB flash disk/USB remove HDD/Network
Pre-alarm Recording	Recording for 10 seconds before alarming
Network Protocol	TCP/IP、PPPOE、DDNS、FTP、NTP and UPNP
Ethernet remote view	Support remote surveillance up to 10 users simultaneously
CMS software	YES
Electronic zoom	YES
Mobilephone View	YES
VGA Interface	YES
Log record function	YES
Image Tour	YES
IR Remote control	YES
Video Loss Detection	YES
Video Adjustable	Hue /Saturation /Contrast /Brightness adjust
PTZ Control	YES
USB Mouse	YES
Power Source	DC 12V
Key Lock(Password Protection)	YES
Power-down recovery function	YES
Size(mm)	259(W) x 44(H) x 221(D)