

Brought to you by



**COMMUNICA**  
*A World of Electronics*


Web: [www.communica.co.za](http://www.communica.co.za) || Email: [info@communica.co.za](mailto:info@communica.co.za)

## Round Standard Key Switch

IGS202A

### DESCRIPTIONS:

- Zinc alloy die cast housing and cylinder.
- Bright chrome plated standard.
- 7 pin tumbler mechanism.
- Steel made tubular keys, nickel plated.
- Key may be withdrawn in one or both positions.
- Silver plated contacts and terminals.
- S202Z 2 position (off-on) 2 tubular terminals.
- S202ZA 2 position (off-on) 2 tubular terminals, spring loaded for momentary contact.
- Hex nut mounted.
- 10000 combinations available.



### SPECIFICATIONS:

- Contact Rating: 4A 125VAC, 2A 250VAC.
- Contact resistance: 10 Milli - Ohms Max.
- Insulation Resistance: 500 Meg - Ohms Min. (500VDC)
- Dielectric Strength: 1500VAC - 1 Minute.

### KEY-PULL FIGURES

- -Off Position
- ┃ -Indicates Key-Pull
- -Indicates No Key-Pull



Fig.1



Fig.2

Fig. No.	Lock Number	Pole	Positions	Terminals	Key Pulls	Turn	↑	→	Type
1	S202Z-1	1	2	2	1	90 eX	Off	On	SPST
2	S202Z-2	1	2	2	2	90 eX	Off	On	SPST
1	S202ZA	1	2	2	1	90 eX	Off	(On)	SPST

\*( ) :Momentary Contact

