

T260D 1000A AC Combination Clamp

- Jaw size 60mm
- Diode
- Continuity buzzer
- Plug-in insulation tester adaptor 500 V DC (Optional) T261

Technical Specification	
AC Current	20,200,1000A
AC Voltage	200,750V
DC Voltage	200m,20,200,1000V
Resistance	200,2K,20K,200K,2M Ω
Accuracy	
DC Voltage	$\pm 0,5\%$ + 1 Digit
AC Voltage	$\pm 1,2\%$ + 10 Digit
AC Current	$\pm 2\%$ + 5 Digit
Resistance	$\pm 1,0\%$ + 2 Digit
Protection	
DC Voltage	1200V DC/ 850 V AC
AC Voltage	1200V DC/ 850 V AC
AC Current	1200A for 60 sec
Resistance	500V AC/DC

Model Specification	
Dimensions (mm)	230(L) x 70(W) x 37(H)
Power Source	9V Battery
Weight	310g

T261 Plug-in Insulation Tester

Technical Specification	
Ranges	20M Ω , 2000M Ω
Accuracy	
20M Ω	2% rdng + 2 Digit
2000M Ω	4% rdng + 2 Digit
Rated Voltage	500V DC

Model Specification	
Dimensions (mm)	90(L) x 70(W)
Power Source	4 x 1.5V AA Batteries
Weight	500g

