

! SiePortal will be unavailable due to maintenance from 9am to 5pm (CEST) on September 7th, 2024. Thanks for your understanding. The SiePortal Team

## SiePortal

The integrated platform for your informatio workflow – bringing together Industry Mall

SiePortal | Region and language

Contact

Help

Support Request

Search for products

> Home > Catalogue > ... > ... > ... > ... > ... > Gauge pressure (pressure series) > 7MF0340-1DM01-5AF2-Z A01+E01+H01

Products & Services

### 7MF0340-1DM01-5AF2-Z A01+E01+H01



Image similar

SITRANS P320 Pressure transmitter Differential pressure and flow PN160 HART (4...20 mA) Measuring cell filling: Silicone oil Maximum measuring span: 60 mbar (24.11 inH<sup>2</sup>O) Oval flange, fastening thread: M10 (PN160), M12 (PN420) Process connection: Stainless steel 316L/1.4404, Seal diaphragms: Stainless steel 316L/1.4404, Sensor differential pressure: Process flange: Stainless steel 316/1.4408 Die-cast aluminum housing Dual chamber device no Ex 2 x M20 x 1.5 With display (lid with glass window) Cable gland and sealing plug attached, metal General approval without Ex approval: World (CE, UKCA, RCM, CSA, EAC, FM, KC) Mounting bracket, electrogalvanised steel

**Notes**

This product cannot be ordered currently. If you need support please contact your Siemens partner

List Price	Show prices
<b>Unit Customer Price</b>	Show prices
Additional Services	For this product we can offer Services like Spare Part Delivery/Repair/Exchange. You have currently no rights to enter the Service Web Shop for that. For further information & to order this service, please contact your local Spares&Repair Partner
Service & Support (Manuals, Certificates, FAQs...)	Download

### Product

Article Number (Market Facing Number)	7MF0340-1DM01-5AF2-Z A01+E01+H01
Product Description	SITRANS P320 Pressure transmitter Differential pressure and flow PN160 HART (4...20 mA) Measuring cell filling: Silicone oil Maximum measuring span: 60 mbar (24.11 inH <sup>2</sup> O) Oval flange, fastening thread: M10 (PN160), M12 (PN420) Process connection: Stainless steel 316L/1.4404, Seal diaphragms: Stainless steel 316L/1.4404, Sensor differential pressure: Process flange: Stainless steel 316/1.4408 Die-cast aluminum housing Dual chamber device no Ex 2 x M20 x 1.5 With display (lid with glass window) Cable gland and sealing plug attached, metal General approval without Ex approval: World (CE, UKCA, RCM, CSA, EAC, FM, KC) Mounting bracket, electrogalvanised steel
Product family	Gauge pressure (pressure series)
Product Lifecycle (PLM)	PM300:Active Product
Notes	This product cannot be ordered currently. If you need support please contact your Siemens partner

### Price data

Price Group / Headquarter Price Group	8P1
List Price	Show prices
Unit Customer Price	Show prices
Metal Factor	None

### Delivery information

Export Control Regulations	ECCN : EAR99H / AL : N
Estimated dispatch time (Working Days)	20 Day/Days
Net Weight (kg)	4,000 Kg
Package size unit of measure	Not available
Quantity Unit	1 Piece
Packaging Quantity	1

### Additional Product Information

EAN	Not available
UPC	Not available
Commodity Code	Not available
LKZ_FDB/ CatalogID	F101-1
Product Group	4770
Group Code	R3P0
Country of origin	France
Compliance with the substance restrictions according to RoHS directive	Since: 17.09.2018
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	
SCIP number	Not available

### Classifications

eClass	Version	Classification
	12	27-20-06-14

eClass	14	27-20-06-14
eClass	6	27-20-06-14
eClass	7.1	27-20-06-14
eClass	8	27-20-06-14
eClass	9	27-20-06-14
eClass	9.1	27-20-06-14
ETIM	7	EC002990
ETIM	8	EC002990
ETIM	9	EC002990

---