

## T2238 Digital Tachometer

- Photo/contact
- Microprocessor based
- High accuracy
- Variable LCD contrast
- Holds last reading/  
recalls max & min

			
TAS35C Surface Speed Test Wheel	TMTL35A Metal Shaft of Cone	TAS35B RPM Adaptor (Funnel)	TA535A RPM Adaptor (Cone)

### Technical Specification

<b>Measurement &amp; Range</b>	Photo: 5 to 99,999 RPM
	Contact: 0,5 to 19,999 RPM
<b>Resolution RPM</b>	Surface Speed (m/min):
	m/min: 0,05 to 1999,9 m/min
	ft/min: 0,2 to 6,560 ft/min
	0,1 RPM (<1,000 RPM)
<b>M/Min</b>	1 RPM ( $\geq$ 1000 m/min)
	0,01 m/min (< 100 m/min.)
<b>Ft/min</b>	0,1 m/min ( $\geq$ 100 m/min.)
	0,1 ft/min. (< 1,000 ft/min.)
	1 ft/min. ( $\geq$ 1,000 ft/min.)
	1 ft/min. ( $\geq$ 1,000 ft/min.)
<b>Display</b>	5 Digits, 10 mm (0,4") LCD
<b>Accuracy</b>	$\pm$ (0,05% + 1 Digit)
<b>Memory</b>	Last/Max/Min value



### Model Specification

<b>Accessories</b>	Carry Case
	Reflecting tape marks (600mm)
	RPM adaptor (cone)
	RPM adaptor (Funnel)
<b>Dimensions (mm)</b>	Surface speed test wheel
	195(L) x 61(W) x 39(H)
<b>Power Source</b>	4 x 1,5V AA Batteries
<b>Weight</b>	280g