




PRODUCT SPECIFICATION


<p>COSMO ELECTRONICS CORPORATION</p>	<p>REED RELAY: D1C240D00</p>	<p>SHEET 1 OF 2</p>
---	---	---------------------

1. OUTSIDE DIMENSION : UNIT (mm)



TOLERANCE : $\pm 0.1\text{mm}$

2. SCHEMATIC : TOP VIEW



PRODUCT SPECIFICATION

COSMO ELECTRONICS CORPORATION	REED RELAY: D1C240D00	SHEET 2 OF 2
---	---------------------------------	--------------

3.0 COIL RATINGS: (AT 20°C)

3.1	Coil resistance	2150	Ω ($\pm 10\%$)
3.2	Nominal coil current	24	VDC
3.3	Maximum Continuous voltage	28	VDC
3.4	Must operate	18	VDC
3.5	Must release	2.4	VDC
3.6	Rated current	11.1	mA

4.0 ELECTRONICAL CHARACTERISTICS:

4.1	Contact resistance	150	m Ω (max)
4.2	Operate time	1.0	ms (max)
4.3	Bounce time	2.0	ms (max)
4.4	Release time	1.0	ms (max)
4.5	Insulation resistance (100 VDC open contact)	10^9	Ω (min)
4.6	Power	3	VA (max)
4.7	Switching voltage	100	VDC (max)
4.8	Switching current	0.25	A (max)
4.9	Carry current	0.5	A (max)
4.10	Breakdown voltage (across open contact)	200	VDC (min)
	(between coil & contact)	500	VDC (min)
4.11	Life expectancy (signal level)	5×10^7	
4.12	Operating temp	-40 to 85°C	
4.13	Storage temp	-50 to 125°C	
4.14	Resonant frequency	3.5	KHZ
4.15	Vibration (10-2000HZ)	20	g (max)
4.16	Minimum permissible load	100	mVDC 10uA