

Brought to you by



COMMUNICA
A World of Electronics


Web: www.communica.co.za || Email: info@communica.co.za

Flat Standard Key Switch

IGS246-1

DESCRIPTIONS:

- Zinc alloy die cast housing and cylinder.
- Yellow chromate plated standard.
- Stainless steel capped bezel with dust shutter mechanism.
- 5 disc tumbler mechanism.
- Reversible double-bitted brass keys, nickel plated.
- Key may be withdrawn in one or both positions.
- Silver plated contacts and terminals.
- S246 2 position (off-on) 2 terminals.
- S246M 2 position (off-on) 2 terminals, spring loaded for momentary contact.
- Hex nut mounted.
- 100 combinations available.



SPECIFICATIONS:

- Contact Rating: 4A 125VAC, 2A 250VAC
- Contact Resistance: 10 Milli-Ohms Max.
- Insulation Resistance: 500 Meg-Ohms Min. (500VDC)
- Dielectric Strength: 1500 VAC - 1 Minute.

KEY-PULL FIGURES

- -Off Position
- ◡ -Indicates Key-Pull
- -Indicates No Key-Pull



Fig. No.	Lock Number	Pole	Positions	Terminals	Key Pulls	Turn	⬆	⬇	Type
1	S246-1	1	2	2	1	90 cX	Off	On	SPST
2	S246-2	1	2	2	2	90 cX	Off	On	SPST
1	S246M	1	2	2	1	90 cX	Off	On	SPST

*():Momentary Contact

Unit: mm

HOLE SIZE

