




# PRODUCT SPECIFICATION


<b>COSMO</b> ELECTRONICS CORPORATION	REED RELAY: <b>D1C120000</b>	SHEET 1 OF 2
---	---------------------------------	--------------

## 1. OUTSIDE DIMENSION : UNIT ( mm )



TOLERANCE :  $\pm 0.1\text{mm}$

## 2. SCHEMATIC : TOP VIEW



# PRODUCT SPECIFICATION

<b>COSMO</b> ELECTRONICS CORPORATION	REED RELAY: <b>D1C120000</b>	SHEET 2 OF 2
---	---------------------------------	--------------

## 3.0 COIL RATINGS: (AT 20°C)

3.1	Coil resistance	500	$\Omega$	( $\pm 10\%$ )
3.2	Nominal coil current	12	VDC	
3.3	Maximum Continuous voltage	20	VDC	
3.4	Must operate	9	VDC	
3.5	Must release	1.2	VDC	
3.6	Rated current	24	mA	

## 4.0 ELECTRONICAL CHARACTERISTICS:

4.1	Contact resistance	150	m $\Omega$	(max)
4.2	Operate time	1.0	ms	(max)
4.3	Bounce time	2.0	ms	(max)
4.4	Release time	1.0	ms	(max)
4.5	Insulation resistance (100 VDC open contact)	$10^9$	$\Omega$	(min)
4.6	Power	3	VA	(max)
4.7	Switching voltage	100	VDC	(max)
4.8	Switching current	0.25	A	(max)
4.9	Carry current	0.5	A	(max)
4.10	Breakdown voltage (across open contact)	200	VDC	(min)
	(between coil & contact)	500	VDC	(min)
4.11	Life expectancy (signal level)	$5 \times 10^7$		
4.12	Operating temp	-40 to 85°C		
4.13	Storage temp	-50 to 125°C		
4.14	Resonant frequency	3.5	KHZ	
4.15	Vibration (10-2000HZ)	20	g	(max)
4.16	Minimum permissible load	100	mVDC	10uA