



**XPS462**

SPECIFICATIONS	
<b>Model</b>	XPS462
<b>Sensor</b>	Low noise high sensitivity dual element rectangular PIR sensor
<b>Sensing Speed</b>	0.2–6 m/second
<b>Operating Temperature</b>	–10°C to 50°C
<b>Power Source</b>	DC10-16V, 12.5mA
<b>Lens</b>	Fresnel vertical protection lens
<b>Protection Range</b>	Distance: 2m, 4m, 6m selectable Height: 3.6m
<b>Mounting Height</b>	Max 3.6m
<b>Mounting</b>	Wall mount or ceiling mount
<b>RFI Protection</b>	Anti RFI, > 20V/m to 1000MHz
<b>Alarm Indication</b>	Red LED on
<b>Alarm Period</b>	3 seconds
<b>Alarm Output</b>	Normal close, 20 ohm internal resistance, 24Vdc 0.1A
<b>Tamper Protection</b>	Normal close, open circuit when cover is removed, contact 0.1A, 24Vdc
<b>Weight</b>	30g
<b>Dimension</b>	28×70x25mm (WxHxD)

**Small Digital Curtain PIR**


**Overview**

The XPS462 is the smallest and most elegant digital curtain-pattern PIR detector using advanced digital True Motion Detection Technology. Once motion signal is received, it compares and analyses the signal with the true motion signal in database memory and ignores extraneous noises in order to eliminate false alarm


**Features**

- Suitable for protection of window, door, balcony and ceiling
- Vertical or horizontal protection
- Microprocessor controlled
- True Motion Detection Technology
- Adjustable range 2-6m
- Fire resistance casing


**Detailed coverage patterns and mounting alternatives**




Wall-Mount Curtain




Ceiling-Mount Curtain



Overhead Curtain



Curtain / Pet Ally



On Internal Door frame