DVR XY9024

24CH H.264 multi-functional standalone DVR





Products Feature

- Compression algorithm upgraded to H.264 High Profile, more advanced video compression technique makes the code stream lowered at least 30%.
- Completely new graphics operating interface design, to let you experience easily and conveniently.
- Super Strong processing capacity: can realize 8CH D1+16CH CIF recording and 16CH playback
- Support main stream and extra steam encode synchronously. Main stream is for local storage to maintain the image quality, extra stream is for network real-time transmission, to easily solve the bottleneck problem of bandwidth.
- Support super cloud service (this function is optional, specialized website forsuper cloud service: www.dvrcenter.net), one step to do remote control easily & conveniently without any complicated setting.
- Powerful net service (support DHCP、PPPOE、FTP、DNS、DDNS、ARSP(www.dvrcenter.com)、NTP、UPNP、EMAIL、IP authority、IP search、alarm center, etc), complete enclosure (WEB、CMS、SDK), to easily achieve interconnection.
- Built-in IE plugs, no need to install from CD disk independently.
- Support 3G & WIFI extension.
- Support multi-browser (IE、Chrome、Firefox、Safari).
- Support all kinds of mobile monitor (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Multiplex operation: Preview, recording, playback, backup, network live, mobile phone view; all operations are independent of each other.
- Support many recording modes: Auto-continuing recording, timing recording, motion detection recording.
- Playback mode support normal play, speed play, fast back play, manual and single-frame play.
- Many backup device: USB flash disk, USB portable HDD and network.
- Support alarm triggered recording will send alerts matter (some models support sending picture) to the designated email.
- Support pre-alarm recording (before 10 sec), not lose any suspicious screen.
- Twenty kinds of language (English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Simplified Chinese, Chinese-Traditional, Turkish, etc.), break up country limitation.
- System auto recovery to power after power reconnected, and return to the pre-power-down state

| | Model | DVR XY9024 |
|---------------------------|-----------------------|---|
| System | Main | Industrial grade embedded micro controller chip Huawei HIS chipset Hi3531 |
| | processor | industrial grade embedded miero controller emp ridawer riis empset riisssi |
| | Operating | Embedded LINUX operating system |
| | system | |
| | System | Multi-channel real-time recording synchronously, multi-channel real-time playback, |
| | resource | multi-channel multi-user network operation, USB back up. |
| | Operation | 16 bit real color GUI interface support mouse operation |
| | interface | (Take all analog input as an average athous are depended on the colorted shaped |
| | Display screen | (Take all analog input as an example, others are depended on the selected channel mode) |
| | | 1/4/9/16/24screen |
| | Video | PAL(625 lines,50fps);NTSC(525lines,60fps) |
| | standard | |
| | Image | |
| | encode | H.264(High Profile) |
| | Monitor | |
| | quality | Monitor: D1; VGA: 1080P; HDMI: 1080P |
| | Playback | Max support 1080P under HVR and NVR mode; Max support D1 under DVR mode |
| Video | quality | wax support 1000F drider HVK and HVK mode; wax support D1 drider DVK mode |
| | Encode | 8CH D1+16CH CIF real time(DVR mode) |
| | capability | |
| | Decode | 8CH D1+8CH CIF real time(DVR mode) |
| | capability | |
| | Multi-mode | DVR mode : 8CH D1+16CH CIF |
| | video input Motion | NVR mode: 24*D1/4*1080P/1*1080P+8*720P/2*1080P+4*720P+4*960H Each channel can set 192(16*12) detection area; can set multi-level of flexibility (for |
| | detection | local analog channel only) |
| Audio | Audio | G.711A |
| | compression | |
| Record | Record | |
| | mode | Manual、alarm、motion detection、timing |
| | Local | Max support 16CH D1 real time playback synchronously (DVR mode) |
| playback | playback | |
| | Video search | Time、date、event、channel search |
| Storage and back up | Space | Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; |
| | occupation | audio: 691.2M/day*channel |
| | Video | Local HDD 、 Network |
| | storage | |
| | Back up | Network backup、USB portable HDD、USB DVD-RW |
| la t | mode | · · |
| Interface | Video input | 24CH BNC |

| | Video output | 2CH BNC,1CH VGA,1CH HDMI |
|-------|-------------------|--|
| | Audio input | 16CH RCA |
| | Audio output | 1CH RCA |
| | Alarm input | 16CH |
| | Alarm output | 2CH |
| | Network port | RJ45 10/100M self-adaptive Ethernet port |
| | PTZ control | 1 RS485; support multi kinds of PTZ Protocol |
| | USB port | 2*USB2.0 |
| | HDD port | 4 SATA |
| | Wireless port | 3G、WIFI(extension via USB port) |
| other | Tour | Yes |
| | Remote controller | Yes |
| | Power | 12V/6A |
| | Dimension | 430(Length) x 370(Width) x 97(Height) |