

### T855 3 Phase Rotation Indicator

- Fused test leads
- Rotating disc
- Colour coded Red/White/Blue
- Large alligator clips



Meter Supplied With Certificate of Conformance

**Technical Specification**

Operating Voltage	90 - 600 VAC
Operating Frequency	50/60 Hz
Operating Temp & Humidity	-10°C to 40°C at 80% Max relative humidity
Cord	1.1m each of Red(R), white(S) & Blue(T)

**Model Specification**

Accessories	Carry Pouch
Dimensions (mm)	106(L) x 75(W) x 40(H)
Weight	515g

### T887 3 Phase Rotation LCD Indicator

- Indicates phase rotation and phase presence
- Colour coded Red/White/Blue
- Large alligator clips



Meter Supplied With Certificate of Conformance

**Technical Specification**

Operating Voltage	40 - 700 VAC
Operating Frequency	50/60 Hz
Operating Temp & Humidity	-1°C to 55°C Not in full sunlight
Cord	60cm each of Red(R), white(S) & Blue(T)

**Model Specification**

Accessories	Carry Pouch
Dimensions (mm)	150(L) x 72(W) x 34(H)
Weight	159g

### T24 - Professional LCR Meter

- Data hold
- Max hold
- Large display



**Technical Specification**

Resistance	20,200,2K,20K,200K, 2M,20MΩ
Capacitance	200p,2n,20n,200n,2μ, 20μ,200μ,2000μF
Inductance	20μ,2μ,20m,200m, 2,20,200H
Diode Test	Diode, LED, Microwave Zener Diode
<b>Accuracy</b>	
Resistance	± 0.3% (20 - 2MΩ)
Capacitance	± 1% (200p - 200nF), 2% (2 - 200μF), ±3% (2000μF)
Inductance	±3% (2m - 200mH)
Overload Protection	25V DC/AC

**Model Specification**

Dimensions (mm)	200(L) x 90(W) x 40(H)
Power Source	9V Battery
Weight	400g

### T8202VB Vibration

- Auto power off
- Magnetic Probe



Optional Accessories: T8202VBS, RS232 Cable, software

**Technical Specification**

Velocity	0,5 ~199,9 mm/s
Acceleration	0,5 ~199,9m/s2
Frequency Range	10hz ~1Khz
<b>Accuracy</b>	
Accuracy	± 5%+2 Digit @23 ±5°C
<b>Protection</b>	
Min &Max Memory	√
Sampling Time	Approx.1 Second
Operating Temperature	0°C ~ 50°C
Operation Humidity	Less Than 80%Rh

**Model Specification**

Accessories	Cables with plugs Sensing probe Magnetic base Carrying case Vibration probe
Optional Accessories	T8202VBS RS232 Cable software
Dimensions (mm)	180(L) x 72(W) x 32(H)
Power Source	9V Battery
Weight	Meter 230g Probe 165g

Meter Supplied With Certificate of Conformance