

T190CB Circuit Breaker Identifier

- Tracing plug sockets to circuit breakers
- Battery check
- Signal strength bar graph



Meter
Supplied With
Certificate of
Conformance

Technical Specification

Operating Voltage	110 - 125 VAC 220 - 240 VAC
Frequency	50 - 60Hz
Transmitter Power	Wall Socket
Receiver Power	9V Battery

Model Specification

Dimensions (mm)	(TX) 200(L) x 60(W) x 45(H)
Dimensions (mm)	(RX) 65(L) x 50(W) x 30(H)
Power Source	(TX) 9 V Battery (RX) Mains
Weight	135g

T330 Digital Thermo Hygrometer Clock

- Time
- Temperature
- Relative humidity (comfort, wet, dry)
- Alarm clock
- Min/Max Temperature and humidity
- Ideal for desktop



Model Specification

Dimensions (mm)	110(L) x 60(W) x 15(H)
Power Source	1 x 1.5V AAA Battery
Weight	20g

T228BT Battery Tester

- LCD bar graph
- 1.5V
- 9V



Model Specification

Dimensions (mm)	84(L) x 38(W) x 20(H)
Power Source	1 x 1.5V AAA Battery
Weight	10g

T7100 Lamp Tester

- Tests gas filled lamps
- Fluorescent lamps
- Neon tubes
- Mercury and metal halogen lamps



Technical Specification

Voltage Test	
Test Range	60 to 250V AC
Frequency	40 to 60Hz
Test Current	< 200mA
Lamp Test	
Voltage	Approx. 3kV/160kHz
Field Strength	Approx. 100µV/m
Display	Red LED test & signal
Continuity Test	
Dielectrical Strength	250V AC/DC
Test Range	Approx. 0 to 5MΩ
Test Current	< 7µA
Display	Red LED test & signal

CAT III
300V
IEC61010-1



Model Specification

Dimensions (mm)	255(L) x 60(W) x 40(H)
Power Source	9V Battery
Weight	170g