


Product Area	Flanschdose, tauchlöten, von vorn verschraubbar M16 connectors IP 67	serie 423/ 723/ 425	Pole	12
			Article number	09 0132 90 12


illustration



scale drawing



Contact Arrangement



	X	Y
A	-0,41	-3,45
B	2,29	-3,61
C	4,10	-1,21
D	3,20	1,34
E	2,71	3,59
F	0,41	3,45
G	-2,29	3,61
H	-4,10	1,21
J	-3,20	-1,34
K	-2,71	-3,59
L	2,00	-1,51
M	-2,00	1,51

You can find the assembly instruction on the next page.

Technical data

Common values

Connector Design	Female socket
Connector locking system	Screw-locking
Termination	dip solder
Wire gauge (mm)	-
Wire gauge (AWG)	-
Max. Cable outlet	-
Upper temperature	+95 °C
Lower temperature	-40 °C

Material

Material of contact	CuSn (bronze)
Contact plating	Au (gold)
Material of contact body	PBT (UL 94 V-0)
Material of housing	zinc diecasting, nickel plated

Cable data

Contacts 12, female socket, dip solder, front fastened, 12 - 19 Contacts, gold plated contacts

Electrical values

Rated voltage	60 V
Rated impulse voltage	500 V
Pollution degree	I
Overvoltage category	I
Material group	III
Rated current (40°C)	3 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shielded
Degree of protection	IP 67
Mechanical operation	>500 mating cycles



Product Flanschdose, tauchlöten, von vorn verschraubbar
Area M16 connectors IP 67 serie 423/ 723/ 425

Pole 12
Article number 09 0132 90 12

Date: 2013-10-04 - Page 2 of 2

Installation instructions / Mounting cutout

