

T235H Electricians DMM

- Large display
- Temperature
- Data Hold
- Capacitance
- Diode
- Continuity

Technical Specification

DC Voltage	200mV,2mV,20,200,1000V
AC Voltage	20V,200V,750V
DC Current	20mA,200mA,20A
AC Current	200mA, 20A
Resistance	200,2K,200K,2MΩ,200MΩ
Temperature	-40°C -1000°C
Capacitance	20nf,2nf,200μF
Accuracy	
DC Voltage	± 0,5 % + 2 Digit
AC Voltage	± 0,8 % + 5 Digit
DC Current	± 1,5 % + 5 Digit
AC Current	± 1,5 % + 5 Digit
Resistance	± 0,8 % + 5 Digit
Temperature	± 0,8 % + 5 Digit
Capacitance	± 2,5 % + 5 Digit
Protection	
AC/DC Voltage	600V DC/AC RMS
AC/DC Current	200mA /250V FUSED 10A 15sec. UNFUSED
Resistance	250V DC/AC RMS <30 sec.
Capacitance	200mA /250V FUSED
Fuse	250mA 250V SELF RESUME



Model Specification

Accessories	Temp Bead Probe
Dimensions (mm)	167(L) x 88(W) x 38(H)
Power Source	9V Battery
Weight	350g

T48 Electronic DMM

- Temperature
- Capacitance
- Transistor
- Diode
- Data hold
- Continuity
- Large display

Technical Specification

DC Voltage	200m,2,20,200,1000V
AC Voltage	200mV,2,20,200,750V
DC Current	2m,20m,200m,20A
AC Current	2mA,20mA,200mA,20A
Resistance	200,2K,200K,2M,200M,2000MΩ
Frequency	2K,20K,200K,2000K,10MHz
Inductance	2m,20m,200m,2,20H
Temperature	-40 to 1000°C
Capacitance	20n,200n,2μ,20μF,200μF
Accuracy	
DC Voltage	±0,5% + 3 Digit
AC Voltage	±0,8% + 3 Digit
DC Current	2m-20mA ± 0,8% + 3 Digit 20A ± 2,0% + 5 Digit
AC Current	20mA ± 1,0% + 5 Digit 20A ± 3,0% + 10 Digit
Resistance	2000mΩ ± 5,0% + 10 Digit
Inductance	200mH ± 2,5% + 20 Digit
Frequency	±5% + 4 Digit
Temperature	±1,5% + 5 Digit
Capacitance	20nf-20μf ±2,5% +20 Digit
Protection	
AC/DC Voltage	1000V DC/AC RMS
AC/DC Current	200mA/250V FUSED 20A 15sec. FUSED
Resistance	250V DC/AC RMS <30 Sec.
Capacitance	36V DC/AC
Frequency	250V DC/AC RMS <10 Sec.
Fuse	250mA 250V SELF RESUME
	12A 250V (20x5)mm



Model Specification

Accessories	Temp Bead Probe
Dimensions (mm)	189(L) x 97(W) x 35(H)
Power Source	9V Battery
Weight	620g

T3601 Electricians DMM

- Large display
- Data hold
- Diode
- Continuity

Technical Specification

DC Voltage	200mV,2V,20,200,1000V
AC Voltage	20V,200V,750V
DC Current	20mA,200mA,20A
AC Current	20mA,200mA,20A
Resistance	200,2K,200K,2MΩ,200MΩ
Temperature	-40°C -1000°C
Capacitance	20nf,2nf,200μF
Accuracy	
DC Voltage	±0,5% + 1 Digit
AC Voltage	±0,8% + 3 Digit
DC Current	20 - 200mA ± 1,5% 20A ± 2,0%
AC Current	20mA-200mA ± 1,5% 20A ± 3,0%
Resistance	200Ω ± 0,8% 2KΩ - 2MΩ ± 0,8% 200mΩ ± 5,0%
Protection	
AC/DC Voltage	600V DC/AC RMS
AC/DC Current	2A /250V FUSED 10A 15 SEC. UNFUSED
Resistance	250V DC/AC RMS <30 sec.
Fuse	250mA 250V SELF RESUME



Model Specification

Accessories	Temp Bead Probe
Dimensions (mm)	167(L) x 88(W) x 38(H)
Power Source	9v Battery
Weight	350g

T7290 Pocket DMM

- Low cost
- 3 1/2 Digit LCD
- Low power consumption
- Diode
- Integral leads
- Continuity

NEW



Technical Specification

AC/ DC Voltage	200m,2,20,200,600V
Resistance	200Ω,2KΩ,20KΩ,200KΩ, 2MΩ,20MΩ
Diode	1,0±0,6 mA 3,2 V max.
Accuracy	
DC Voltage	±0,8% + 1 Digit
AC Voltage	±1,5% + 1 Digit
Resistance	±0,8% + 4 Digit
Diode	± 2,0% + 2 Digit

Model Specification

Dimensions (mm)	109(L) x 56(W) x 14(H)
Power Source	2 x 1,5V LR44 (T515Batt)
Weight	110g