

Brought to you by



**COMMUNICA**  
*A World of Electronics*

Web: [www.communica.co.za](http://www.communica.co.za) || Email: [info@communica.co.za](mailto:info@communica.co.za)

**Flat Standard Key Switch**

**IGS332**



**DESCRIPTIONS:**

- Zinc alloy die cast housing and plastic cylinder.
- Bright chrome plated standard.
- 3 disc tumbler mechanism.
- Brass keys, nickel plated, with plastic cover.
- Key may be withdrawn in one or both or three positions.
- Silver plated contacts and terminals.
- S331 2 position (on-on) 60 index 3 terminals.
- S332 2 position (off-on) 60 index 2 terminals.
- S333 3 position (off-on-on) 60 index 3 terminals.
- Hex nut or speed clip mounted.
- 16 combinations available.

**KEY-PULL FIGURES**

- -Off Position
- ▮ -Indicates Key-Pull
- -Indicates No Key-Pull




Fig. No.	Lock Number	Pole	Positions	Terminals	Key Pulls	Turn	⬆	↗	⬇	Type
1	S331	1	2	3	2	60 cX	On	On	i @	SPDT
2	S332	1	2	2	2	60 cX	Off	On	i @	SPST
3	S333	1	3	3	3	120 cX	Off	On	On	SPDT

Unit: mm

HOLE SIZE

