

## Photo:



## Main Features:

- 1/3" 1.3Megapixel progressive scan Aptina CMOS
- H.264 video compression
- Max 25/30fps@720P(1280×720)
- Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS & DMSS
- 3.6~16mm Daiwon megapixel varifocal lens
- Max IR LEDs length 20m
- Compatible with ONVIF and PSIA standards
- DC12V

## Specifications:

Model	<b>XY IPCAM 35CVD1.3 POE</b>
Camera	
Sensor	1/3" Progressive Scan CMOS
Min.Illumination	Color: 0.1Lux @(F1.2,AGC ON, Sensor Up) B/W: 0.01Lux @(F1.2,AGC ON, Sensor Up)
Shutter	1/25s ~ 1/100,000s
Lens Mount	3.6~16mm megapixel lens
Auto Iris	Manual
Day/Night	ICR
Compression	

Standard	H.264 / MJPEG
Output Bit Rate	32Kbps~16Mbps
Audio Standard	G.711
<b>Picture</b>	
Max Size	1280 × 720
Frame	50Hz: 25fps (1280×720) 60Hz: 30fps (1280×720)
Setup	Saturation, Brightness, Contrast could be adjusted from CMS or IE
<b>Network</b>	
Storage	Support SD/SDHC,NAS(iSCSI optional)
Alarming	Motion detection, Network lost, IP Conflict, HDD full, HDD wrong
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE , SMTP,NTP ONVIF/PSIA
Others	Key Reset, Anti-Flicking, Dual-Stream, Password Protection, Water-Print
<b>Connection</b>	
Audio Input	1CH Mic, 3.5mm Audio Input
Audio Output	1CH, 3.5mm Audio Output(600Ω)
Protocol	1 RJ45 10M/100M, 1 RS-485
Alarm Input	1CH
Alarm Output	/
Video Output	1Vp-p Composite Output(75Ω/BNC)
<b>General</b>	
Tem & Hud	-10℃~60℃, Humdity less than 90%
Power	POE
Consumption	4.5W MAX(ICR On,9.5W MAX) -W: 6W MAX(ICR On,11W MAX)
Dimmension(mm)	68 × 64.9 × 144.8
Weight	1000g