


Product Area	Female socket with wires, front fastened, 0,5 mm ² M12 connectors A-Coding serie 713/763	Pole	8
		Article number	09 3482 116 08

illustration



scale drawing



Ausführung mit Zink Druckgussgehäuse
Version with zinc diecasted housing

Contact Arrangement



geschirmt/ shielded	nicht geschirmt/ not shielded
1 weiß/white	1 weiß/white
2 braun/brown	2 braun/brown
3 grün/green	3 grün/green
4 gelb/yellow	4 gelb/yellow
5 grau/grey	5 grau/grey
6 rosa/pink	6 rosa/pink
7 blau/blue	7 blau/blue
8 Gehäuse-Schirm/ Housing-shield	8 Schirm/shield

You can find the assembly instruction on the next page.

Technical data

Common values

Connector Design	Female socket
Connector locking system	Screw-locking
Termination	wires
Wire gauge (mm)	0,25 mm ²
Wire gauge (AWG)	24
Upper temperature	+85 °C
Lower temperature	-40 °C

Material

Material of contact	CuSn (bronze)
Contact plating	Au (gold)
Material of contact body	PA
Material of housing	zinc diecasting, nickel plated

Cable data

Contacts 8: Female socket with wires, front fastened, 0,5 mm², PG 9

Electrical values

Rated voltage	60 V
Rated impulse voltage	800 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	2 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 68
Mechanical operation	>100 mating cycles



Product Female socket with wires, front fastened, 0,5 mm²
Area M12 connectors A-Coding serie 713/763

Pole 8
Article number 09 3482 116 08

Date: 2013-10-04 - Page 2 of 2

Installation instructions / Mounting cutout

Mit Durchgangsbohrung/*With bore hole*

