

Brought to you by




**COMMUNICA**  
*A World of Electronics*

Web: [www.communica.co.za](http://www.communica.co.za) || Email: [info@communica.co.za](mailto:info@communica.co.za)

**Flat Standard Key Switch**

**IGS286B-2**



**DESCRIPTIONS:**

- Zinc alloy die cast housing and cylinder. Chrome plated.
- 5-Disk tumblers mechanism.
- Reversible double cut key brass made nickel plated.
- Silver plated contacts and terminals.
- S286A 2 Positions 4 Terminals. (2NO, 2NC.)
- S286B 2 Positions 4 Terminals. (1NO, 1NC.)
- Anti-static switch also available 20 KVDC protection.

**SPECIFICATIONS:**

- Contact Rating: 4A 125VAC, 2A 250VAC.
- Contact Resistance: 10 Milli-Ohms Max.
- Insulation Resistance: 500 Meg-Ohms Min. (500 VDC)
- Dielectric Strength: 1500 VAC-1 Minute.

**KEY-PULL FIGURES**

- o -Off Position
- I -Indicates Key-Pull
- -Indicates No Key-Pull





Fig. No.	Lock Number	Pole	Positions	Terminals	Key Pulls	Turn	⊕	⊖	Type
1	S286A-1	2	2	4	1	90°	Off	On	DPST
2	S286A-2	2	2	4	2	90°	Off	On	DPST
3	S286B-1	2	2	4	1	90°	On	On	DPDT
4	S286B-2	2	2	4	2	90°	On	On	DPDT

-13-

Unit: mm

HOLE SIZE

