

## Photo:



## Main Features:

- 1/3" 1.3Megapixel progressive scan Aptina CMOS
- H.264 video compression
- Max 25/30fps@720P(1280×720)
- Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS & DMSS
- 2.8~11mm megapixel varifocal lens
- Max IR LEDs length 30m
- Compatible with ONVIF and PSIA standards
- DC12V

## Specifications:

|                    |   |
|--------------------|---|
| Model              | <b>XY IPCAM 35CV1.3</b>   |
| <b>Camera</b>      |   |
| Sensor             | 1/3" Progressive Scan CMOS  |
| Min.Illumination   | Color: 0.1Lux @(F1.2,AGC ON, Sensor Up)<br>B/W: 0.01Lux @(F1.2,AGC ON, Sensor Up) |
| Shutter            | 1/25s ~ 1/100,000s  |
| Lens Mount         | 2.8~11mm megapixel lens   |
| Auto Iris          | Manual  |
| Day/Night          | ICR   |
| <b>Compression</b> |   |
| Standard           | H.264 / MJPEG   |

|                   |   |
|-------------------|---|
| Output Bit Rate   | 32Kbps~16Mbps   |
| Audio Standard    | G.711   |
| <b>Picture</b>    |   |
| Max Size          | 1280 × 720  |
| Frame             | 50Hz: 25fps (1280×720)<br>60Hz: 30fps (1280×720)                        |
| Setup             | Saturation, Brightness, Contrast could be adjusted from CMS or IE       |
| <b>Network</b>    |   |
| Storage           | Support SD/SDHC,NAS(iSCSI optional)                                     |
| Alarming          | Motion detection, Network lost, IP Conflict, HDD full, HDD wrong        |
| Protocol          | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE , SMTP,NTP<br>ONVIF/PSIA       |
| Others            | Key Reset, Anti-Flicking, Dual-Stream, Password Protection, Water-Print |
| <b>Connection</b> |   |
| Audio Input       | 1CH Mic, 3.5mm Audio Input  |
| Audio Output      | 1CH, 3.5mm Audio Output(600Ω)   |
| Protocol          | 1 RJ45 10M/100M, 1 RS-485   |
| Alarm Input       | 1CH   |
| Alarm Output      | /   |
| Video Output      | 1Vp-p Composite Output(75Ω/BNC)   |
| <b>General</b>    |   |
| Tem & Hud         | -10℃~60℃, Humdity less than 90%   |
| Power             | DC12V±10%   |
| Consumption       | 4.5W MAX(ICR On,9.5W MAX)<br>-W: 6W MAX(ICR On,11W MAX)                 |
| Dimmension(mm)    | 68 × 64.9 × 144.8   |
| Weight            | 1000g   |