

XY WIFI CAM OD2812PTZ

Features:

- 2M 1/3" SC2235 low illumination CMOS sensor;
- Support for mobile video surveillance(iOS,android);
- Video occupied space super small;
- Support thousands of people online at the same time to watch;
- Clear and bright industry leader;
- Support multiple display modes;
- With AP hot spots; no wireless router can control;

Model	XY WIFI CAM OD2812PTZ
Embedded Processor	MSTAR MSC313E
sensor	SC2245/1080P
Lens	2.8~12MM
Image pixels	1080P, 2.0 Megapixel
LED	6 units IR LED
Distance	50M
Minimum illumination	4500mV/Lux-s 0.01Lux@F2.0, black/white 0.001Lux@F2.0
Day and night	IR-cut double filter automatic switching
Rotation Range	Pan: 0~350º, Tilt:0~93º,
Rotation Speed	Pan: 0~35º/s, Tilt:0~25º/s,
Preset	6pcs
Auto Flip	N/A
Video coding	H.265 ,dual stream
Video frame rate	25frame/second
Audio coding	ADPCM , support two way voice intercom
network interface	1 RJ45 10M/100M adaptive Ethernet ports;
Wireless standard	IEEE802.11b/g/n
Frequency range	2.4GHz ~ 2.4835 GHz
ONVIF	NO
Storage port	1pcs TF (Micro SD) storage port , max 128G (class10)
Reset port	Master reset
Power supply and consumption	DC 12V/2.5A
Working condition	-10°C~+50°C@humidity 10%~ 95% no condensation
	Support IOS/Android; Support the use of mobile phones to view real-time video, real-time recording, and playback video;
	Support local screen shots by mobile app;
APP function	Support push alarm information screen shot ;